



CWNA-108^{Q&As}

Certified Wireless Network Administrator

Pass CWNP CWNA-108 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/cwna-108.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

You are troubleshooting an issue reported by several wireless users. The problem is contained to one cell (several users connected to the same AP). You manage the WLAN and no other network devices. After analysis it appears to be a switch problem. What action should be taken?

- A. Create a plan of action and implement it
- B. Escalate the problem to the network administration team
- C. Document the results and close the case
- D. Escalate the problem to the wireless vendor support staff

Correct Answer: B

QUESTION 2

ABC Company is planning to install a new 802.11ac WLAN, but wants to upgrade its wired infrastructure first to provide the best user experience possible. ABC Company has hired you to perform the RF site survey. During the interview with the network manager, you are told that the new Ethernet edge switches will support VoIP phones and 802.11 access points, both using 802.3 PoE.

After hearing this information, what immediate concerns do you note?

- A. The power budget in the edge switches must be carefully planned and monitored based on the number of supported PoE devices.
- B. The edge Ethernet switches should support Ether-channel to get the best results out of the network.
- C. VoIP phones and 802.11 access points should not be powered by the same edge switch due to distortion.
- D. If the switches are in optimal locations for VoIP phones, they are likely to be suboptimal locations for 802.11 APs

Correct Answer: A

QUESTION 3

A WLAN is implemented using wireless controllers. The APs must locate the controllers when powered on and connected to the network. Which one of the following methods is commonly used to locate the controllers by the APs?

- A. DHCP
- B. GRE
- C. NTP
- D. SNMP

Correct Answer: A

**Reference**

https://books.google.com.pk/books?id=YEW0DAAAQBAJandpg=SA7-PA9andlpg=SA7-PA9anddq=methods+is+commonly+used+to+locate+the+controllers+by+the+APsandsource=blandots=O2sMDIjjDVandsig=M1_gvQnGaWfGg13Pbb1xTkflkIAandhl=enandsa=Xandved=0ahUKEwj3hvmPoaLZAhWRPFAKHb5MAyQQ6AEIJzAA#v=onepageandq=methods%20is%20commonly%20used%20to%20locate%20the%20controllers%20by%20the%20APsandf=false

QUESTION 4

You are deploying a WLAN with the access points configured for 10 mW of output power on the 2.4 GHz radios and 20 mW of output power on the 5GHz radios. Some semi-directional antennas are also in use. What kind of deployment is described?

- A. SOHO
- B. Residential
- C. High density
- D. Standard office

Correct Answer: A

QUESTION 5

To ease user complexity, your company has implemented a single SSID for all employees. However, the network administrator needs a way to control the network resources that can be accessed by each employee based in their department.

- A. RBAC
- B. SNMP
- C. WIPS
- D. WPA2

Correct Answer: A

[Latest CWNA-108 Dumps](#)

[CWNA-108 PDF Dumps](#)

[CWNA-108 Brindumps](#)