



DES-4121^{Q&As}

PowerEdge Specialist Exam for Implementation Engineer

Pass EMC DES-4121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/des-4121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

After a disk rebuild operation, a technician needs to configure the system so that the rebuild process happens faster in the future, even at the expense of slowing users down. How should the technician perform this task?

- A. Change the System Profile to Performance in the System BIOS Settings
- B. Change the Rebuild Rate in the System BIOS Settings
- C. Change the System Profile to Performance in the iDRAC GUI
- D. Change the Rebuild Rate from the iDRAC GUI

Correct Answer: C

QUESTION 2

A technician wants to move memory from a few older systems into a newer system. What is the most efficient method to accomplish this task?

- A. Power down all of the older servers to physically check the memory Move any matching memory to the new server
- B. Use iDRAC to view the memory details of the older systems Power down the servers to move matching memory to the new server
- C. Back up the server profile on the older server Move the matching memory and import the server profile to the new server
- D. Power down any of the older servers to move any memory to the new server Update BIOS to allow mismatched memory

Correct Answer: D

QUESTION 3

A technician is creating a virtual disk in the DRAC (2x 4 TB NL-SAS in RAID 1) to install Windows 2016. They manually boot to the OS installation media without using the Lifecycle Controller OS Deployment wizard. Only the first 2048 GB on the virtual disk can be partitioned.

How should the technician obtain access to the remaining 2 TB (approximately) of storage?

- A. Delete the 4 TB virtual disk and create a virtual (boot) disk no longer than 2048 GB.
- B. Upgrade to a newer version of the operating system.
- C. Use the lifecycle Controller's OS Deployment Wizard to deploy the OS on this server.
- D. Use F2 to go into the BIOS, change the BIOS boot mode to UEFI, and try again.

Correct Answer: C

**QUESTION 4**

A server is equipped with 2 CPUs and 12x 8 GB DIMMs, for a total of 96 GB. The OS is not seeing all the memory. Which memory mode should be configured so that all memory is seen by the OS?

- A. Mirroring
- B. Advanced ECC
- C. Optimizer
- D. Sparing

Correct Answer: C

Reference <https://www.dell.com/support/article/pk/en/pkbsd1/sln155709/memory-modes-in-dualprocessor-11th-generation-powerededge-servers?lang=en#Sparing>

QUESTION 5

A server is configured with a RAID 5 Virtual Disk across five hard disks and one spare disk. If a hard disk failure occurs within the RAID 5 virtual disk, the spare disk needs to be online as quickly as possible. It is acceptable for users to experience decreased performance during the rebuild procedure.

How should this requirement be met?

- A. Enable Rebuild Priority
- B. Increase Rebuild Rate
- C. Change cache to Write Through
- D. Select Fast Rebuild

Correct Answer: A

[Latest DES-4121 Dumps](#)

[DES-4121 PDF Dumps](#)

[DES-4121 Practice Test](#)