



DES-4122^{Q&As}

Specialist - Implementation Engineer PowerEdge Version 2.0

Pass EMC DES-4122 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/des-4122.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

DRAG DROP

Match each RAID level to its characteristic.

Select and Place:

| Level | Characteristic |
|---------|--|
| RAID 10 | Highest disk overhead |
| RAID 5 | Failure of one drive affects overall performance |
| RAID 6 | Requires minimum of four drives |
| RAID 1 | Used for high performance databases |

Correct Answer:

| Level | Characteristic |
|-------|----------------|
| | RAID 10 |
| | RAID 6 |
| | RAID 1 |
| | RAID 5 |

QUESTION 2

A Dell EMC PowerEdge server logs the following CPU Machine Check error CPU1 IERR What action might solve the problem?

- A. Remove flea power
- B. Update the Intel driver



- C. Reseat the IDSDM
- D. Swap the PERC controller

Correct Answer: B

QUESTION 3

An engineer is checking a newly delivered Dell EMC PowerEdge R640 server that will be deployed for a new database environment

The inventory consists of:

- 1 PowerEdge R640 Server
- 1 Hot-plug Power Supply, 750W - qty 1
- Jumper Cord - C13/C14, 4M, 250V, 10A - qty 1
- Broadcom 57412 Dual Port 10GbE SFP+ and 5720 Dual Port 1GbE BASE-T rNDC - qty 1
- SFP+ SR Optic, 10GbE - qty 2
- Dell Networking, Cable, SFP+ to SFP+, 10GbE, Copper Twinax DAC, 3 Meter - qty 2
- CAT6 Patch cable 5 Meters - qty 2

The server power configuration will be set for gnd redundancy The management switch is 1000 Base-T and the top of rack switches 10Gb

What additional component(s) is needed for this configuration?

- A. Hot-plug power supply, 750 W - qty 1
- B. Hot-plug power supply, 1100W - qty 1
- C. Dell Networking, cable, 40GbE (QSFP+) to 4 x 10GbE SFP+ passive copper breakout cable, 3 meters - qty 2
- D. C20 to C21, PDU style, 250 V, 16 Amp, 3 5 meters power cord - qty 2

Correct Answer: D

QUESTION 4

What is the drive characteristic of a BOSS M.2 drive in a Dell EMC PowerEdge server?

- A. Single-level cell
- B. Read Intensive
- C. Quad-level cell
- D. Write Intensive

Correct Answer: A



QUESTION 5

What must be done before upgrading OMSA from the 32-bit to the 64-bit version?

- A. Save the license file
- B. Disable UAC
- C. Back up the configuration
- D. Uninstall the earlier version

Correct Answer: A

[Latest DES-4122 Dumps](#)

[DES-4122 VCE Dumps](#)

[DES-4122 Exam Questions](#)