



DES-4122^{Q&As}

Specialist - Implementation Engineer PowerEdge Version 2.0

Pass EMC DES-4122 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/des-4122.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which processor configuration is used by the Dell EMC PowerEdge R740 server?

- A. 4 socket AMD
- B. 2 socket AMD
- C. 2 socket Intel
- D. 4 socket Intel

Correct Answer: C

QUESTION 2

A Dell EMC PowerEdge 14G server uses Intel OPTANE DC Persistent Memory in App Direct mode. What is the minimum size DIMM supported for this type of memory?

- A. 64 GB
- B. 128 GB
- C. 256 GB
- D. 512 GB

Correct Answer: C

QUESTION 3

What can be done using in-band management?

- A. Agentless discovery
- B. Firmware and driver updates
- C. Network bandwidth optimization
- D. Remote access

Correct Answer: C

QUESTION 4

An engineer needs to upgrade a Dell EMC PowerEdge R440 server from a single PSU to dual PSU configuration. There are unused PSU modules from PowerEdge R430 and R420 servers available, and they have the same wattage ratings.

What should the engineer do to complete the task?



- A. Add the PowerEdge R420 PSU modules to the PowerEdge R440
- B. Order a new PSU specific to the existing PowerEdge R440
- C. Add the PowerEdge R430 PSU modules to the PowerEdge R440
- D. Configure the PowerEdge R440 PSU with 1+1 configuration

Correct Answer: A

QUESTION 5

A company that has very specific firmware requirements has acquired Dell EMC PowerEdge servers. Any replaced parts of the type must match the original parts identically. The procedure must be as simple as possible with minimal risk.

What action should a technician take to help accomplish this goal?

- A. Configure servers to access the remote firmware repository
- B. Enable the Match Firmware of Replaced Part setting in the system BIOS
- C. Install and configure a repository manager
- D. Enable the Collect System Inventory On Restart (CSIOR) attribute

Correct Answer: A

[DES-4122 Practice Test](#)

[DES-4122 Study Guide](#)

[DES-4122 Braindumps](#)