



DES-5121^{Q&As}

Specialist - Implementation Engineer - Campus Networking Exam

Pass EMC DES-5121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/des-5121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Refer to the Exhibit.

```
Switch-1(config)# radius server host 10.1.1.111 Switch-1(config-radius)# key "secretkey" Switch-1(config-radius)# exit
Switch-1(config)# aaa authentication login "LOCAL-AUTH" local Switch-1(config)# aaa authentication login "REMOTE-
AUTH" radius local Switch-1(config)# aaa authentication enable "REMOTE-AUTH" radius enable Switch-1(config)# aaa
authentication login default tacacs local Switch-1(config)# aaa authentication enable default tacacs enable
Switch-1(config)# line telnet Switch-1(config-telnet)# login authentication "REMOTE-AUTH" Switch-1(config-telnet)# exit
Switch-1(config)# line ssh Switch-1(config-ssh)# login authentication default Switch-1(config)# exit Switch-1(config)# line
console Switch-1(config-line)# login authentication "LOCAL-AUTH" Switch-1(config-line)# exit
```

Which authentication method will be used if a user tries to log into the switch when accessing through SSH?

- A. RADIUS, then fails over to a local user account
- B. Local user account
- C. TACACS, then fails over to a local user account
- D. None

Correct Answer: C

QUESTION 2

Which interface on a Dell EMC N-Series switch provides the most security for management?

- A. VLAN
- B. Ethernet
- C. Loopback
- D. Out-of-band

Correct Answer: D

QUESTION 3

A user's workstation is connected to an IP phone that is connected to a Dell EMC N-Series switch. Which type of traffic is typically tagged or untagged?

- A. Data = tagged, Voice = untagged
- B. Data = untagged, Voice = untagged
- C. Data = tagged, Voice = tagged
- D. Data = untagged, Voice = tagged



Correct Answer: D

Reference: <https://www.dell.com/support/article/en-us/how12385/how-to-enable-the-voice-vlan-feature-on-dell-emc-networking-n-series-switches?lang=en>

QUESTION 4

A user's workstation has an IP phone connected to a Dell EMC N-Series switch.

What is the recommended number of VLANs that should be configured on the switch port?

- A. 0
- B. 1
- C. 2
- D. 3

Correct Answer: C

QUESTION 5

A network has two switches with the following IP addresses:

Switch1: 192.168.1.240

Switch2: 192.168.1.241

The administrator wants to add VRRP on an existing switch configuration using the virtual IP 192.168.1.240.

What is a VRRP requirement for this configuration?

- A. Priority 241 on Switch2
- B. Priority 255 on Switch1
- C. Virtual Router ID 1
- D. Virtual Router ID 240

Correct Answer: B

[Latest DES-5121 Dumps](#)

[DES-5121 Practice Test](#)

[DES-5121 Exam Questions](#)