



DES-5121^{Q&As}

Specialist - Implementation Engineer - Campus Networking Exam

Pass EMC DES-5121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/des-5121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

What is the maximum number of dynamic MAC addresses that can be learned on a Dell EMC N-Series switchport that is configured for dynamic locking?

- A. 100
- B. 300
- C. 400
- D. 600

Correct Answer: A

Reference: <https://www.dell.com/support/article/en-us/how10392/how-to-configure-mac-based-port-security-on-dell-n2000-n3000-and-n4000-series-switches?lang=en>

QUESTION 2

When configuring a PBR route-map, what are the configurable "SET" options?

- A. set ip source, set ip next-hop, and set ip default next-hop
- B. set ip next-hop, set ip source, and set ip precedence
- C. set ip next-hop, set ip default next-hop, and set ip precedence
- D. set ip source, set ip default next-hop and set ip precedence

Correct Answer: C

QUESTION 3

To which destination MAC address are MLAG peer-keepalive packets sent?

- A. 01:00:B5:00:00:00
- B. 01:00:C5:00:00:00
- C. B5:00:01:00:00:00
- D. C5:00:01:00:00:00

Correct Answer: A

Reference: <https://www.manualslib.com/manual/858353/Dell-Networking-N4000-Series.html?page=941>

QUESTION 4



DRAG DROP

What is the typical sequence of steps to upgrade the firmware of a Dell EMC N-Series switch?

Select and Place:

Copy the firmware image from the TFTP server to the switch	Step 1
Configure and start the TFTP server	Step 2
Update the boot code on the switch and reboot	Step 3
Backup the running-config to a TFTP server	Step 4
Select the new image for the next boot	Step 5

Correct Answer:

	Configure and start the TFTP server
	Backup the running-config to a TFTP server
	Copy the firmware image from the TFTP server to the switch
	Select the new image for the next boot
	Update the boot code on the switch and reboot

QUESTION 5

What is the IP protocol number, in decimal, assigned by IANA for VRRP?



- A. 25
- B. 112
- C. 443
- D. 1443

Correct Answer: B

[DES-5121 VCE Dumps](#)

[DES-5121 Practice Test](#)

[DES-5121 Braindumps](#)