



DES-6322^{Q&As}

Specialist - Implementation Engineer-VxRail Exam

Pass EMC DES-6322 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/des-6322.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

For which typical activity would the Full data migration setting be used when placing a VxRail host into maintenance mode?

- A. Temporary maintenance
- B. Rebooting a single ESXi host
- C. Shutting down an entire cluster
- D. Permanently removing host from cluster

Correct Answer: A

QUESTION 2

What is a difference between vSAN Data-In-Transit Encryption and vSAN Data-At-Rest-Encryption?

- A. Data-In-Transit Encryption: Encrypts traffic between VMs and the VxRail nodes Data-At-Rest Encryption: Encrypts traffic between VxRail nodes only
- B. Data-In-Transit Encryption: Does not require a Key Management Server Data-At-Rest Encryption: Requires a Key Management Server
- C. Data-In-Transit Encryption: Key Management Server must reside on the vSAN cluster Data-At-Rest Encryption: Key Management Server can reside on the vSAN cluster
- D. Data-In-Transit Encryption: Addresses fear of media theft Data-At-Rest Encryption: Addresses fear of rogue administrators

Correct Answer: A

QUESTION 3

DRAG DROP

What is the correct sequence of steps to perform a RASR Factory Reset using an SD card?

Select and Place:



Boot the node from the internal SD card	Step 1
Acknowledge the Warning and Caution messages, then type "Disconnected" to proceed	Step 2
Access iDRAC and launch virtual console to the VxRail node	Step 3
Quit the RASR menu and reboot the system	Step 4
Select F – Factory Reset in the RASR Menu	Step 5

Correct Answer:



	Access iDRAC and launch virtual console to the VxRail node
	Quit the RASR menu and reboot the system
	Acknowledge the Warning and Caution messages, then type "Disconnected" to proceed
	Boot the node from the internal SD card
	Select F – Factory Reset in the RASR Menu

QUESTION 4

An implementation engineer is deploying a new VxRail cluster. What should they confirm before installing the hardware?

- A. Service laptop must be on the same IP network as the iDRACs
- B. At least 36 in (92 cm) clearance exists in front of and behind the cabinet
- C. Power distribution must support the power rating of a single node
- D. Single power zone must be used with adequate power cables

Correct Answer: C

QUESTION 5

What is the recommended format for host names when using the VxRail Deployment Wizard for an External vCenter solution?



- A. FQDN for vCenter Server Host name for VxRail Manager
- B. Host name for both vCenter Server and for VxRail Manager
- C. FQDN for both vCenter Server and for VxRail Manager
- D. Host name for vCenter Server FQDN for VxRail Manager

Correct Answer: A

Reference: <https://www.delltechnologies.com/asset/en-us/products/converged-infrastructure/technical-support/h15300-vxrail-network-guide.pdf>

[DES-6322 PDF Dumps](#)

[DES-6322 Practice Test](#)

[DES-6322 Exam Questions](#)