



DES-6322^{Q&As}

Specialist - Implementation Engineer-VxRail Exam

Pass EMC DES-6322 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/des-6322.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is the correct CLI command to collect only the vCenter logs on VxRail Manager?

- A. vc-support.sh -v
- B. generateFullBundle.py -v
- C. vc-support-bundle.sh -c
- D. generateLogBundle.py -c

Correct Answer: D

Reference: <https://davidring.ie/2021/01/14/vxrail-7-0-useful-log-file-information/>

QUESTION 2

What is a valid 2-node VxRail cluster configuration?

- A. 2x 10 GbE and 2x 25 GbE in a switch configuration and external vCenter
- B. 2x 1 GbE and 2x 10 GbE in a direct-connect configuration and external vCenter
- C. 2x 1 GbE and 2x 10 GbE in a switch configuration and internal vCenter
- D. 2x 10 GbE and 2x 25 GbE in a direct-connect configuration and internal vCenter

Correct Answer: B

Reference: <https://www.delltechnologies.com/asset/en-us/products/converged-infrastructure/technical-support/h17566-vsant2node-cluster-on-vxrail-planning-guide.pdf> (P.5)

QUESTION 3

Which VxRail Series is designed to support a VDI environment and requires a GPU card in each host?

- A. S Series
- B. V Series
- C. G Series
- D. P Series

Correct Answer: A

Reference: <https://www.arrow.com/ecs-media/13768/h18599-vdi-and-ai-in-healthcare-reference-architecture.pdf>



QUESTION 4

Which vSAN feature requires an All-Flash cluster?

- A. Deduplication and compression
- B. Data-at-Rest Encryption
- C. Data-in-Transit Encryption
- D. Storage Policy Based Management

Correct Answer: A

QUESTION 5

An implementation engineer is deploying a new VxRail cluster. What should they confirm before installing the hardware?

- A. Service laptop must be on the same IP network as the iDRACs
- B. At least 36 in (92 cm) clearance exists in front of and behind the cabinet
- C. Power distribution must support the power rating of a single node
- D. Single power zone must be used with adequate power cables

Correct Answer: C

[Latest DES-6322 Dumps](#)

[DES-6322 Practice Test](#)

[DES-6322 Braindumps](#)