VCE & PDF
Pass4itSure.com

E20-326^Q&As

Symmetrix Solutions Design Exam for Technology Architects Exam

Pass EMC E20-326 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/e20-326.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

SATISFACTION GUARANTEED
100%
SATISFACTION GUARANTEED

QUESTION 1

You have used BCSD to model an SRDF/S solution. What information can be obtained from the model?

A. Bandwidth requirement, RA utilization, and volume exceptions

B. RA utilization, DA and cache utilization, and host service time

C. Cache utilization, RA utilization, and potential problem volumes

D. Bandwidth requirement, RA utilization, and network latency

Correct Answer: A

QUESTION 2

You need to model several SRDF/A workloads that require data consistency across all the sessions. How would you model the multiple SRDF/A sessions?

A. In BCSD, link them by creating a Composite Group

B. In SymmMerge, link them by creating a Composite Group

C. In BCSD, link them by creating a Logical Relationship

D. In SymmMerge, link them by creating a Logical Relationship

Correct Answer: A

QUESTION 3

You are implementing a FAST VP solution for a customer and want to start with a conservative FAST VP relocation rate. What would be the recommended value for the relocation rate?

A. 4

B. 7

C. 10

D. 1

Correct Answer: D

QUESTION 4

Refer to the exhibit.

```
Symmetrix ID: 000192613164
Optimizer and FAST Control Parameters:
Data Movement Mode : User_Approve
Max Simultaneous Device Moves : 8
Max Device Moves Per Day : 200
Optimizer, FAST and FAST VP Control Parameters:
Min Initial Workload Period(hrs) : 24
Workload Analysis Period(hrs) : 128
FAST Control Parameters: Swap Not Visible Devices : Disabled
Allow Only Swap : Disabled
FAST VP Control Parameters:
FAST VP Data Movement Mode : AUTO
FAST VP Data Relocation Rate : 5
Thin Pool Reserved Capacity(%) : 10
VP Allocation By FAST policy : N/A
FAST VP Time to Compress : Never
FAST VP Compression Rate : N/A
```

A customer has a Symmetrix VMAX storage array configured with FAST VP using three storage tiers. Policies are active for all storage groups on the array. The customer would like to increase the size of data movement requests. The current configuration of FAST is shown in the exhibit.

Which parameter should be changed?

A. Data Relocation Rate

B. Max Simultaneous Moves

C. Max Moves per Day

D. Data Movement Mode

Correct Answer: A

QUESTION 5

Which operations are allowed by Open Replicator/LM?

A. Online pull only

B. Offline pull only

C. Online push only

D. Offline push only

Correct Answer: A