



# E20-326<sup>Q&As</sup>

Symmetrix Solutions Design Exam for Technology Architects Exam

## Pass EMC E20-326 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/e20-326.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

A customer has taken four snaps of a TimeFinder/Snap source device at 10:00 a.m., 1:00 p.m.,

3:00

p.m. and 5:00 p.m. A restore operation is performed at 8:00 p.m. from the 5:00 p.m. snap session. What is the first step needed to create a snap from the same source device at 9:00 p.m.?

A.

Terminate the restored session

B.

Terminate all snap sessions

C.

Terminate the 5pm session

D.

Create a 9pm snap session

Correct Answer: A

### QUESTION 2

You are designing the Symmetrix VMAX architecture for a DAS-to-SAN SQL Server migration. Currently all user databases reside on a single locally-attached disk enclosure, mounted to "M:". You have decided on RAID-1 protected 15,000 RPM drives for the new SQL environment.

Last week, you configured Perfmon to record the current IOPS load of the databases during the 8-hour business day, Monday through Friday as shown in the exhibit. During an average business day, the transaction log processes 43 GB worth of data.

Day 1		Day 2		Day 3		Day 4		Day 5	
Read	Write	Read	Write	Read	Write	Read	Write	Read	Write
858	1036	1067	903	1010	921	877	1078	841	855
1082	958	971	961	1047	1159	899	892	1080	956
829	1022	904	884	786	998	1191	917	1132	1146
780	1032	1123	879	877	1022	944	1130	981	1088
1165	1167	1079	1026	786	988	781	1076	841	1052
825	1113	758	1080	898	1140	984	1196	954	880
1152	994	894	921	817	1060	1036	980	930	994
1001	1175	762	1133	971	1200	1091	907	1045	997

Following EMC best practices, which discount can be taken from the overall write IOPS when calculating for the database writes?



A. 196

B. 392

C. 597

D. 989

Correct Answer: A

---

### QUESTION 3

A customer has a pair of VMAX arrays configured to replicate thin devices at one site to thin devices at another site using SRDF/A. The customer wants to implement TimeFinder/Clone replication of the R1 device on the source array and asks you to confirm this is a supported configuration. What do you advise the customer?

A. Yes, it is supported.

B. It is supported only if the precopy option is used.

C. No, it is not supported.

D. It is supported only if composite groups are used.

Correct Answer: A

---

### QUESTION 4

What is considered to be a thin unfriendly environment?

A. an environment that makes use of filesystems that append data instead of re-using free space.

B. an environment that contains databases that make use of the auto-extend capability.

C. an environment that is used for media and document repositories.

D. an environment that is used by Test Development and Quality Assurance.

Correct Answer: A

---

### QUESTION 5

What is a Capacity Available for Active Replication (CAAR) consideration when using TimeFinder on a Symmetrix VMAX?

A. TimeFinder VP Snap requires 2X protection slots for source and 1X protection slots for up to 16 targets

B. TimeFinder/Snap requires protection slots for both source and target

C. TimeFinder/Snap source requires 2X the protection slots of the target



D. TimeFinder VP Snap requires 2X protection slots for both source and target for up to 32 targets

Correct Answer: A

[E20-326 PDF Dumps](#)

[E20-326 VCE Dumps](#)

[E20-326 Exam Questions](#)