



E20-507^{Q&As}

VMAX3 Solutions Specialist Exam for Storage Administrators

Pass EMC E20-507 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/e20-507.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A VMAX3 parent Storage Group (SG) contains two child SGs: SG1 and SG2. What is a valid bandwidth limit setting for this cascaded Storage Group?

A. Parent SG

Correct Answer: A

QUESTION 2

Which Solutions Enabler environment variable allows the command output to match a previous version of Solutions Enabler?

A. symcli_mode

B. symcli_output_mode

C. symcli_noprompt

D. symcli_command_scope

Correct Answer: A

Reference: <http://ireland.emc.com/collateral/TechnicalDocument/docu68922.pdf>

QUESTION 3

Which SYMCLI command(s) can be used to set/modify Host I/O limits?

A. symsg only

B. symconfigure and symaccess

C. symaccess only

D. symaccess and symsg

Correct Answer: A

Reference: <https://community.emc.com/thread/188068?start=0andstart=0>

QUESTION 4

On a VMAX3 array, a TDEV is provisioned to a host using a Storage Group that has no SLO defined. How will the TDEV be handled by FAST?



- A. Optimized SLO will be applied to the TDEV
- B. FAST will not manage the TDEV
- C. TDEV will be pinned to the middle tier
- D. TDEV will be Not Ready

Correct Answer: A

QUESTION 5

Storage has been provisioned from a VMAX3 using a Masking View with a single Storage Group associated with the Bronze SLO. How can new storage be provisioned to this host using the Gold SLO while maintaining the original volumes in the Bronze SLO?

- A. Convert the existing Storage Group to cascaded, create a new child Storage Group for the new devices, and apply the Gold SLO.
- B. Apply the Gold SLO directly to the new volumes.
- C. Add a cascaded Storage Group to the original Storage Group and apply the Gold SLO.
- D. A new Masking View and Storage Group is required for the devices managed by the Gold SLO.

Correct Answer: A

[E20-507 PDF Dumps](#)

[E20-507 Practice Test](#)

[E20-507 Study Guide](#)