



E20-542^{Q&As}

VMAX3 Solutions and Design Specialist Exam for Technology Architects

Pass EMC E20-542 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/e20-542.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A customer has production and disaster recovery VMAX3 arrays. There is limited bandwidth between the sites. The amount of data which will be replicated by using SRDF to the disaster recovery site is slightly more than the available bandwidth allows.

Which action is needed to accommodate the customer's need?

- A. Install an optional compression module
- B. Enable the compression license
- C. Enable compression on the RA Director
- D. Enable the Fast Write feature on the SRDF Group

Correct Answer: A

QUESTION 2

After an SRDF failover operation, production work has been moved to the remote site. A large number of invalid tracks have accumulated that need to be synchronized back to the R1 volumes.

Which SRDF operation can reduce the re-synchronization time, while continuing production work on the remote site?

- A. Update
- B. Failback
- C. Restore
- D. Establish

Correct Answer: A

QUESTION 3

The Reserved Capacity for a Storage Resource Pool (SRP) on a VMAX3 has been set to 15%. A TimeFinder SnapVX snapshot has been created for a Storage Group containing 10 devices. An application is actively performing read and write I/Os to these devices. The snapshot is linked to the target in Copy mode. Allocation for the SRP reaches 85%.

What will happen to the copy process?

- A. Copy to the target will halt
- B. Copy to the target will fail
- C. Tracks required for the copy will be allocated from the Reserved Capacity



D. Copy to the target will continue and complete

Correct Answer: A

QUESTION 4

You have configured Open Replicator between a new VMAX3 array and a VMAX. A host is connected to the VMAX3 array and a control device is configured to pull data from a remote device on the VMAX. You want the host to be able to access data on the control device while the data is being pulled from the remote device. What will cause writes to the control device to be propagated back to the remote device?

- A. Donor Update
- B. Copy-On-First Access
- C. Front-end Zero Detecton
- D. Background Copy

Correct Answer: A

QUESTION 5

A customer wants to implement SRDF/S for an application. The application is performing at 10,000 IOPS and is using many volumes. The size of the I/O is 4 KB. Forty percent (40%) of the IOPS are writes. Assume an RA can handle a maximum of 4,000 4 KB IOPS. Based on best practice, how many RAs should be recommended?

- A. 1
- B. 2
- C. 4
- D. 8

Correct Answer: B

[Latest E20-542 Dumps](#)

[E20-542 PDF Dumps](#)

[E20-542 Exam Questions](#)