



# E20-616<sup>Q&As</sup>

Symmetrix Installation and Troubleshooting Specialist

## Pass EMC E20-616 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/e20-616.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

When using TimeFinder/Clone, when does the target device become read/write available to the target host?

- A. After Activation
- B. During the Create Session process
- C. After a full background copy completes
- D. Before Activation

Correct Answer: A

---

**QUESTION 2**

Refer to the Exhibit.

### Server Rear



You are implementing ESRS. Into which Ethernet port do you plug the IP cable?

- A. 8
- B. 7
- C. 6
- D. 5

Correct Answer: A

---

**QUESTION 3**

A customer plans to upgrade an existing four-Engine Symmetrix VMAX 40K to a five-Engine VMAX 40K. How many new vault devices will be added as a result of this upgrade?



A. 32

B. 40

C. 64

D. 80

Correct Answer: A

---

#### QUESTION 4

Which action needs to be taken if the Backend Cabling Verification fails after a Data Center relocation?

A. Contact PSE Lab for assistance.

B. Relocate the cables shown as faulted.

C. Replace the cables shown as faulted.

D. Power down and re-start the Backend Cabling Verification script.

Correct Answer: A

---

#### QUESTION 5

You are installing a VMAX 40K with dispersed System Bay.

Which length cables are required to provide back-to-back separation?

A. 25M

B. 10M

C. 3.6M

D. 20M

Correct Answer: A

[E20-616 VCE Dumps](#)

[E20-616 Study Guide](#)

[E20-616 Exam Questions](#)