



# H11-828<sup>Q&As</sup>

HCNP-UC(Fast Track)(Unified Communication (Fast Track))

## Pass Huawei H11-828 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/h11-828.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

The administrator can export the account file from the BMU, modify account information in the account file, and upload the modified file to the BMU to modify account information in the directory in batches.

- A. TRUE
- B. FALSE

Correct Answer: A

---

**QUESTION 2**

In the eSpace Audio Recorder solution, HWLogIMP works in ( ) mode.

- A. C/S
- B. B/S
- C. A/S
- D. A/A

Correct Answer: A

---

**QUESTION 3**

In the disaster recovery scenario, when the primary node is faulty, which of the following statements are CORRECT? (Multiple Choice)

- A. On the standby node, you can run the `show connectstates stationtype primaryserver` command to query the connection status between the primary and standby nodes.
- B. The status of the connection to the primary node is displayed as disconnected on the standby node.
- C. On the standby node, you can run the `show workstatus` command to query the working status of the primary node.
- D. The working status of the standby node is Deactivate.

Correct Answer: AB

---

**QUESTION 4**

The eSpace UC solution provides end-to-end security networking schemes, including (). (Multiple Choice)

- A. Signaling encryption
- B. Open interfaces



- C. Media stream encryption
- D. Distributed networking in peer-to-peer mode

Correct Answer: AC

---

#### QUESTION 5

A U1981 has been deployed in an enterprise and connects to the PSTN through the PRA trunk. After an incoming call from an external user is routed through the PRA trunk, to disallow the external user to call other external users, it is recommended that the outgoing call permission of the trunk be set to ().

- A. Intra-office call
- B. Local call
- C. National toll call
- D. International toll call

Correct Answer: A

[H11-828 Practice Test](#)

[H11-828 Study Guide](#)

[H11-828 Exam Questions](#)