



# H12-211<sup>Q&As</sup>

HCIA-Routing & Switching V2.2

**Pass Huawei H12-211 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/h12-211.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

The following is true about PPP description (). (multiple choice)

- A. For the physical layer, PPP supports asynchronous links and synchronous links.
- B. PPP is not scalable and cannot be deployed on an Ethernet link.
- C. PPP supports plaintext and ciphertext authentication
- D. PPP supports multiple network layer protocols, such as IPCP and IPXCP.
- E. PPP supports bundling multiple physical links into logical links to increase bandwidth

Correct Answer: ACDE

---

**QUESTION 2**

system-view [Huawei]command-privilege level 3 view user save

Refer to the command output. What is the result of the shown command?

- A. The command adjusts the save command of a user to privilege level 3.
- B. The command adjusts the save command in the user view to privilege level 3.
- C. The command adjusts the user view command privilege level to 3, and saves the configuration.
- D. The command adjusts the privilege level of a user to 3, and saves the configuration.

Correct Answer: B

---

**QUESTION 3**

Refer to the graphic. The data is transmitted using IPsec tunnel mode. The fields of which headers will be authenticated?

- A. TCP and Data
- B. Origin IP, TCP and Data
- C. AH, Origin IP, TCP and Data
- D. The fields of all headers

Correct Answer: C

---

**QUESTION 4**



NAPT allows for multiple internal addresses to be mapped to a single public address. How does NAT distinguish between the different private addresses when mapping to the same public address?

- A. The source MAC address is used.
- B. The destination MAC address is used.
- C. The source port number is used.
- D. The destination port number is used.

Correct Answer: C

### QUESTION 5

As shown in the figure, two hosts communicate between VLANs through one-arm routing. When the G0/0/1.2 sub-interface of RTA receives host B and sends it to host A. Which of the following operations does RTA perform when data frames?



- A. RTA forwards the data frame directly through the G0/0/1.1 subinterface.
- B. After the RTA deletes the VLAN tag 20, it is sent out by the G0/0/1.1 interface.
- C. RTA first deletes VLAN tag 20, then adds VLAN tag 10, and then sends it out through G0/0/1.1 interface.
- D. RTA will discard the data frame

Correct Answer: C



VCE & PDF

Pass4itSure.com

<https://www.pass4itsure.com/h12-211.html>

2024 Latest pass4itsure H12-211 PDF and VCE dumps Download

---

[Latest H12-211 Dumps](#)

[H12-211 PDF Dumps](#)

[H12-211 Practice Test](#)