



# H12-222<sup>Q&As</sup>

HCIP-Routing & Switching-IENP V2.5

**Pass Huawei H12-222 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/h12-222.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

When the stateful inspection firewall forwards subsequent data packets (non-first packet), which of following table is used for forwarding?

- A. Routing table
- B. MAC address table
- C. Session table
- D. FIB table

Correct Answer: C

---

**QUESTION 2**

In a MPLS VPN network, two-layer MPLS labels are added to data packets before they are transmitted over the public network. Which of the following statements regarding two-layer labels are false? (Multiple Choice)

- A. The outer label is the private network label and the inner label is the public network label.
- B. The MPLS VPN outer label is distributed manually by the LDP protocol. The inner label is distributed by the peer MP-BGP neighbor.
- C. By default, the outer label in data packets is popped out before being forwarded to the last hop.
- D. The outer label is used to instruct the PE to send data packets to the correct VPN.

Correct Answer: AD

---

**QUESTION 3**

Simple traffic classification uses the DSCP priority of IP packets, the EXP priority of MPLS packets, and 802.1p priority of VLAN packets.

- A. TRUE
- B. FALSE

Correct Answer: A

---

**QUESTION 4**

Which of the following statements regarding traffic policing is true? (Multiple Choice)

- A. Packets cannot be colored.
- B. Packets can be colored.



- C. The packets of which the rate is exceeded can be buffered.
- D. The packets of which the rate is exceeded cannot be buffered.

Correct Answer: BD

---

#### QUESTION 5

A DHCP server provides different address allocation modes to meet various application requirements. Which address allocation mode can be used to allocate an IP address to a host requiring temporary network access or allocate a group of limited IP addresses that can be shared by a group of temporary hosts?

- A. Automatic allocation
- B. Dynamic allocation
- C. Manual allocation
- D. Manual or dynamic allocation

Correct Answer: B

[H12-222 PDF Dumps](#)

[H12-222 VCE Dumps](#)

[H12-222 Braindumps](#)