



H12-222^{Q&As}

HCIP-Routing & Switching-IENP V2.5

Pass Huawei H12-222 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/h12-222.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

The WRED drop profile defines the following parameters for AF21 traffic: the lower drop threshold is 35, the upper drop threshold is 40, and the maximum drop probability is 50%. Which of the following statements regarding the processing result of AF21 traffic are false? (Multiple Choice)

- A. When the average length of packets in the queue is smaller than 35, packets are discarded.
- B. When the average length of packets in the queue is larger than 35 and smaller than 40, the drop probability of packet is 50%.
- C. When the average length of packets in the queue is larger than 40, packets enter the queue.
- D. When the average length of packets in the queue is larger than 40, packets are discarded.

Correct Answer: AC

QUESTION 2

Which of the following statements regarding Huawei eSight network management software is false?

- A. eSight is a lightweight system and a wizard is available for eSight installation.
- B. eSight adopts the C/S architecture, so users can access eSight using a browser anytime, anywhere.
- C. eSight provides corresponding solutions for different customers.
- D. eSight can uniformly manage devices from multiple vendors.

Correct Answer: B

QUESTION 3

In the SDN network architecture, which device is used to calculate the path and deliver the flow table?

- A. Application server
- B. Controller
- C. Orchestrator
- D. Device

Correct Answer: B

QUESTION 4

The following describes the VPN configuration on a device. Which of the following statements is true?



```
vpn-target 1:1 export-extcommunity  
vpn-target 2:2 import-extcommunity
```

- A. This command is configured on the CE of the customer network.
- B. route-distinguisher 1:1 indicates that the RD value is 1:1, which is not globally unique.
- C. vpn-target 1:1 export-extcommunity indicates that the Export Target of the VPN is 1:1.
- D. vpn-target 2:2 import-extcommunity indicates that the Import Target of the VPN is 2:2. Only one value can be set for the Import Target.

Correct Answer: C

QUESTION 5

```
[SR1] mpls lsr-id 1.1.1.0  
[SR1] mpls  
[SR1] interface g1/0/1/0  
[SR1-ge1/0/1/0] mpls  
[SR1-ge1/0/1/0] quit  
[SR1] static-lsp ingress SR1SD destination 4.4.4.32 next-hop 10.1.1.2 out-label 20
```

The following figure shows the configuration. Which of the following statements are false? (Multiple Choice)

- A. The mpls lsr-id command configures the LSR ID. This command is the prerequisite for other MPLS commands. By default, this command is not configured.
- B. The mpls command can be run in the system view and interface view to enable MPLS. You can configure a LSR ID after MPLS is enabled.
- C. After MPLS is enabled globally, you do not need to enable MPLS in the interface view again.
- D. The last command configures LSRA as the ingress LSR and creates a static LSP.

Correct Answer: BC

[Latest H12-222 Dumps](#)

[H12-222 VCE Dumps](#)

[H12-222 Study Guide](#)