



H12-321^{Q&As}

HCIP-WLAN-CEWA V1.0

Pass Huawei H12-321 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/h12-321.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is the correct description of RF resource management below?

- A. The propagation of wireless electromagnetic waves in the air will cause the wireless signal to attenuate due to the influence of the surrounding environment, which will affect the quality of wireless users' access to the Internet. Therefore, RF resource management is required.
- B. By configuring RF resource management, RF resources can be dynamically adjusted to adapt to changes in the wireless signal environment.
- C. By configuring radio resource management, you can improve the user's online experience.
- D. You can improve the security of user access by configuring radio resource management.

Correct Answer: ABC

QUESTION 2

If a small AP that can accommodate up to 90 people is deployed with 3 APs, the CAC can be configured on each AP to limit the number of users to 30. If the SSID is hidden, the load balancing between APs can be implemented indirectly.

- A. Correct
- B. False

Correct Answer: A

QUESTION 3

Regarding the 802.1X authentication method, is the following description correct?

- A. 802.1X authentication mode is divided into EAP termination and EAP transparent transmission.
- B. EAP transparent authentication requires the NAS device to identify and resolve key information in the EAP and map it to the RADIUS packet to complete the entire authentication.
- C. EAP termination authentication does not require the NAS to resolve EAP packets. Instead, the EAP is encapsulated in RADIUS packets, so that authentication packets traverse the encapsulated network and reach the authentication server.
- D. EAP transparent authentication is also called EAP relay authentication.

Correct Answer: AD

QUESTION 4

On a WLAN with the WIDS function enabled, APs with the following MAC addresses are detected:



01-01-22-22-33-33

02-01-01-22-33-33

02-01-01-22-33-34

02-01-22-01-01-22

OUI 01-01-22 has been added to the whitelist.

Which of these APs will be identified as rogue APs? (Multiple Choice)

A. 01-01-22-22-33-33

B. 02-01-01-22-33-33

C. 02-01-01-22-33-34

D. 02-01-22-01-01-22

Correct Answer: BCD

QUESTION 5

Regarding the Agile Controller admission model, what is the correct description below?

A. In the admission model, the core is the authorization condition and authorization result

B. Currently only 802.1x and Portal authentication can support all the conditions in the admission model.

C. Authorization element does not include IP address range

D. Authorization conditions include authorization elements

Correct Answer: ABD

[Latest H12-321 Dumps](#)

[H12-321 PDF Dumps](#)

[H12-321 Study Guide](#)