



H12-321^{Q&As}

HCIP-WLAN-CEWA V1.0

Pass Huawei H12-321 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/h12-321.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

As shown in the figure, in the Mesh networking, what is required to enable the STP spanning tree protocol?

- A. AC G0/0/1 interface
- B. MPP
- C. MP
- D. Switch

Correct Answer: D

QUESTION 2

On WLANs where many users exist, such as WLANs in high density scenarios, users compete fiercely to occupy channels as the number of online users increases. As a result, network quality deteriorates. To ensure network access experience of online users, Calling Access Control (CAC) can be configured. CAC allows an AP to control user access based on the CAC thresholds set according to the radio channel usage, number of online users on a radio, or terminal signal-to-noise ratio (SNR), ensuring network access quality of online users.

- A. TRUE
- B. FALSE

Correct Answer: A

QUESTION 3

Which of the following statements are TRUE about band steering supported by Huawei devices? (Multiple Choice)

- A. Load balancing between the 2.4 GHz and 5 GHz radios is considered in band steering. An AP determines the radio with which a STA preferentially associates based on numbers of access users on the 2.4 GHz and 5 GHz radios.
- B. Check whether the number of access users on an AP exceeds the start threshold for load balancing between radios. If not, STAs can preferentially associate with the 5 GHz radio.
- C. If the number of access users on an AP exceeds the start threshold for load balancing between radios, the AP determines the frequency band to which the STA connects based on radio load difference computed according to the formula (Number of access users on the 5 GHz radio - Number of access users on the 2.4 GHz radio / Number of access users on the 5 GHz radio x 100%).
- D. After the number of users associated with an AP reaches the start threshold for load balancing between radios, if the value obtained based on the formula (Number of access users on the 5 GHz radio - Number of access users on the 2.4 GHz radio / Number of access users on the 5 GHz radio x 100%) is greater than the gap-threshold value, the AP preferentially associates with the STA on the 5 GHz radio.

Correct Answer: ABC



QUESTION 4

On a WLAN, which of the following attack detection functions require support of the dynamic blacklist function? (Multiple Choice)

- A. Flooding attack detection
- B. Spoofing attack detection
- C. Weak IV attack detection
- D. Brute force attack detection

Correct Answer: AD

QUESTION 5

Which access authentication methods are supported by the Agile Controller?

- A. 802.1x certification
- B. Portal authentication
- C. MAC certification
- D. RADIUS

Correct Answer: ABC

[H12-321 PDF Dumps](#)

[H12-321 Practice Test](#)

[H12-321 Exam Questions](#)