



H12-811^{Q&As}

HCIA-Datacom V1.0

Pass Huawei H12-811 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/h12-811.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

In the network as shown in the figure, the administrator hopes that all hosts cannot access the Web service (the port number is 80). Other services can be accessed normally. Then, in the interface configuration of G0/0/1, traffic-filter Which ACL rule needs to be bound to the outbound?



- A. acl number 3000 Rule 5 deny tcp destination-port eq www Rule 10 permit ip #
- B. acl number 3001 Rule 5 deny udp destination-port eq www Rule 10 permit ip #
- C. acl number 3002 Rule 5 permit ip Rule 10 deny tcp destination eq www #
- D. acl number 3003 Rule 5 permit ip Rule 10 deny udp destination eq www #

Correct Answer: BD

QUESTION 2

The output information of the routing table of a certain router is shown in the figure. Which of the following statements is correct? () (Multiple Choice Questions)

R1display ip routing-table

Route Flags: R-relay, D-download to fib

Routing Tables: Public

Destinations: 10 Routes: 10

Destination/Mask	Proto	Pre	Cost	Flags	NextHop	Interface
10.0.0.0/8	Static	60	0	RD	10.0.12.2	Ethernet0/0/0
10.0.2.2/32	Static	60	0	RD	10.0.21.2	Ethernet0/0/1

- A. The NextHop for this router to reach 10.0.2.2 is 10.0.12.2
- B. The NextHop for this router to reach 10.0.0.1 is 10.0.12.2
- C. The NextHop for this router to reach 10.0.2.2 is 10.0.21.2
- D. The NextHop for this router to reach 10.0.0.1 is 10.0.21.2

Correct Answer: BC

**QUESTION 3**

After a fault occurs in the network, the administrator finds that the configuration of a certain router has been modified through troubleshooting. What measures should the administrator take to avoid this situation from happening again? (*)

- A. The administrator should configure ACL to control that only the administrator can log in to the device
- B. The administrator should enable port-security on the routed management port
- C. The administrator should configure AAA. to authenticate and authorize users who log in to the device
- D. The administrator should configure the permission level of all accounts except the administrator to log in to the device as

Correct Answer: ACD

QUESTION 4


Which of the following IEEE802.11 standards only supports the 24GHz frequency band for communication? ()

- A. 802.11g
- B. C. 802.11ax
- C. 802.11a

Correct Answer: B

QUESTION 5

The network shown in the figure below. The administrator wants RTA to use a static router. Priority is given to sending data packets to RTB's Loopback0 interface through G0/0/1 port. At the same time, G0/0/2 is used as a backup. Then any configuration on RTA can be Realize this requirement? () (Single-choice question)



- A. ip route-static 10.0.2.2 255.255.255.255 10.0.12.2 ip route-static 10.0.2.2 255.255.255.255 10.0.21.2 preference 40
- B. ip route-static 10.0.2.2 255.255.255.255 10.0.12.2 ip route-static 10.0.2.2 255.255.255.255 10.0.21.2
- C. ip route-static 10.0.2.2 255.255.255.255 10.0.12.2 preference 70 ip route-static 10.0.2.2 255.255.255.255 10.0.21.2
- D. ip route-static 10.0.2.2 255.255.255.255 10.0.12.2 ip route-static 10.0.2.2 255.255.255.255 10.0.21.2 preference 70

Correct Answer: D



VCE & PDF

Pass4itSure.com

<https://www.pass4itsure.com/h12-811.html>

2024 Latest pass4itsure H12-811 PDF and VCE dumps Download

[H12-811 VCE Dumps](#)

[H12-811 Study Guide](#)

[H12-811 Braindumps](#)