

# H12-831<sup>Q&As</sup>

HCIP-Datacom-Advanced Routing & Switching Technology V1.0

## Pass Huawei H12-831 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/h12-831.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Huawei Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





#### **QUESTION 1**

The Router LSA of a router is shown in the figure. Which of the following statements is wrong?

- A. of this routerRouter IDfor10.0.12.1
- B. This router isDR
- C. This router has established an adjacency relationship
- D. This router supports external route import

Correct Answer: B

#### **QUESTION 2**

If faced with a complex network failure, and it is estimated that the troubleshooting cannot be completed in a short period of time, and the user urgently needs to restore the availability of the network, then the correct approach is.

- A. Tell the user it\\'s not possible
- B. Directly build an alternative network environment without notifying customers
- C. Always try to troubleshoot without informing the user of the current troubleshooting difficulty
- D. Communicate with users whether it is possible to skip the faulty node and build an alternative network environment

Correct Answer: D

#### **QUESTION 3**

Regarding the BGPI MPLS IPVPN network architecture, which of the following descriptions is wrong?

A. PThe device only needs to have the basicM PLSForwarding capability, not maintainedVPNRelated Information

B. between sites viaVPNMutual visits, a site can only belong to1indivualVPN

C. In general,CEThe device does not perceiveVPNexistence, andCEDevice does not require supportMPLS,MP-BGP Wait

D. BGP/MPLS IP VPNnetwork architecture byCE(CustomerEdge).PE(ProviderEdge)and P( Provider)consists of three parts, includingPEandPis operator equipment,CEYesBGP/MPLS IPVPNUser settings prepare

Correct Answer: B

#### **QUESTION 4**



What is the most efficient way to view device alarms through the CLI?

- A. display interface brief
- B. display clock
- C. display alarm
- D. display current-configuration

Correct Answer: C

#### **QUESTION 5**

According to this figure, which statement is correct about the IPv6 routing information calculated by the R4 router through IS-IS?

### Public Routing Table: ISIS

```
Summary Count2
```

Destination

NextHop FE80::2E0:FCFF:FE982576

Cost

Interface GigabitEthemetO/O/O

Destination

NextHop PE8C ZeOFC-FFEA \*813 Cost 10

Destination ....

NextHop:FE80::2E0:FCFF:FE98i2576

Cost

Destination:-

PrefixLength: 0

NextHop : FE80 2E0:FCFF:FEA7:5813


Cost

interface GigabitEthernetO/O/1

Prefix L ength: 0

Preference 15

Protocol : IS/S-LJ



PrefixLength 0

Preference: 15

Protocol: ISJS-L1

Preference : 15

ProtocoJ : ISiS-L I



- A. day4have1stripIS-ISdefault route
- B. R4have2equivalentIS-ISdefault route
- C. R4have2not equivalentIS-ISdefault route
- D. R4withoutIS-ISrouting entry for

Correct Answer: B

Latest H12-831 Dumps

H12-831 Practice Test H12-831 Exam Questions