



# H12-891<sup>Q&As</sup>

HCIE-Datcom V1.0

## Pass Huawei H12-891 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/h12-891.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

When you troubleshoot a local area network with Huawei equipment deployed, you find that there are a large number of unicast frames with unknown source AC addresses in the local area network . A large number of unknown source MAC addresses single-plug frames can cause the switch the biggest danger is ?

- A. Memory that occupies the cache ton
- B. Increases the power consumption of the power supply
- C. Consumes a TCAM table entry
- D. Consume the available bandwidth
- E. Consume the MAC address table entry available in the system

Correct Answer: E

---

**QUESTION 2**

When deploying BGP/MPLS IPVPN, OSPF\\'s VPN route tag is not present.

The extended properties of MP-BGP are passed only locally, only locally, and only meaningful on routers that receive MP-BGP routes and generate OSPF LSAs.

- A. TRUE
- B. FALSE

Correct Answer: A

---

**QUESTION 3**

Two routers connected through a firewall cannot establish a BGP neighbor relationship. What causes it?

- A. EBGP Multi-hop is not configured
- B. The firewall did not release IP protocol number 89
- C. Firewalls that do not have an open UDP port number of 179
- D. BGP neighbors must form a Layer 2 adjacency

Correct Answer: C

---

**QUESTION 4**

About multi-instance CE (Multi-VPN-Instance CE, MCE). What is the error described below?



- A. Users who connect to the same MCE but are not part of a VPN instance cannot access each other
- B. The MCE vs. PE direction must have multiple physical links to achieve isolation between different VPN instances
- C. MCE-enabled devices can access multiple VPI instances in BGP/RPLS IPVPN applications, reducing user network equipment investment
- D. On the MCE device, you need to create their own routing tables for different VPNs and bind to the corresponding interface

Correct Answer: B

### QUESTION 5

Two routers, connected together through the serial port, but can not ping between each other , now check the port status as follows: Can the following information determine what the cause is?

```
[R1]display interface ge 0/0/0
Serial0/0/0 current state : UP
Line protocol current state : DOWN
Description:
Route Port, The Maximum Transmit Unit is 1500, Hold timer is 10(sec)
Internet Address is 12.12.12.1/24
Link layer protocol is nonstandard HDLC
Last physical up time : 2018-08-01 16:24:01 UTC-08:00
Last physical down time : 2018-08-01 16:24:00 UTC-08:00

[R2]display interface Serial 0/0/0
Serial0/0/0 current state : UP
Line protocol current state : DOWN
Description:
Route Port, The Maximum Transmit Unit is 1500, Hold timer is 10(sec)
Internet Address is 21.21.21.2/24
Link layer protocol is PPP
LCP stopped
```

- A. Insufficient link bandwidth
- B. The IP addresses on both ends are not on the same network segment
- C. The link layer protocols on both ends are inconsistent
- D. Subnet mask does not match the

Correct Answer: C

[H12-891 PDF Dumps](#)

[H12-891 VCE Dumps](#)

[H12-891 Exam Questions](#)