

H31-124_V2.0^{Q&As}

HCIP Carrier IP V2.0

Pass Huawei H31-124_V2.0 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass4itsure.com/h31-124_v2-0.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



https://www.pass4itsure.com/h31-124_v2-0.html

2024 Latest pass4itsure H31-124_V2.0 PDF and VCE dumps Download

QUESTION 1

Which of the following statements are correct?

- A. Both TE FRR and VPN FRR are used to protect tunnels, and therefore they can replace each other.
- B. After VPN FRR is deployed, the end-to-end service convergence time is shorter than 1 second.
- C. TE FRR Implements quick traffic switchovers if a PE becomes faulty.
- D. VPN FRR implements quick traffic switchovers if a PE becomes faulty.

Correct Answer: B

QUESTION 2

The Ethernet switch working in store and forward mode drops the frame with length smaller than 64 bytes.

- A. True
- B. False

Correct Answer: A

QUESTION 3

When router receives two instances of one LSA at the same time, it will first compare LS age, If same ,Uien compare LS Sequence number.

- A. True
- B. False

Correct Answer: B

QUESTION 4

Which of the following statements about layer 2 LAN switch are incorrect?

- A. LAN switch will modify the data link layer header of the packet and then forward it.
- B. LAN switch can learn Mac address automatically.
- C. LAN switch operates at data link layer.
- D. LAN switch will modify the network layer header of the packet and then forward it.

Correct Answer: B

https://www.pass4itsure.com/h31-124_v2-0.html 2024 Latest pass4itsure H31-124_V2.0 PDF and VCE dumps Download

QUESTION 5

Which of the following operations need to be complete before IP FRR configuration?

- A. Configure different costs to generate two routes with different costs.
- B. Configure the same cost to generate two equal-cost routes.
- C. Configure a dynamic routing protocol on the entire network to Implement IP connectivity between nodes.
- D. Configure static routes or an IGP to implement IP connectivity between nodes.

Correct Answer: C

<u>Latest H31-124 V2.0</u> <u>Dumps</u> H31-124 V2.0 VCE Dumps H31-124 V2.0 Practice Test