



H31-124_V2.0^{Q&As}

HCIP Carrier IP V2.0

Pass Huawei H31-124_V2.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/h31-124_v2-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

LDP uses Initialization message to negotiate LDP parameters with the peer.

A. True

B. False

Correct Answer: A

QUESTION 2

VXLAN uses MAC in UDP encapsulation to extend Layer 2 networks and encapsulates Ethernet packets on IP packets. When packets are transmitted on a routed network, the intermediate routing device does not need to learn inner MAC addresses.

A. True

B. False

Correct Answer: B

QUESTION 3

If Adjacency Segment + Node Segment is used together, the entire path can be forced to include an adjacency and load balancing. This mode is called loose path.

A. True

B. False

Correct Answer: B

QUESTION 4

PIM-SM relies on particular unicast routing protocol for RPF check.

A. True

B. False

Correct Answer: B

QUESTION 5

Which of the following statements regarding DIS election is correct?



- A. When the priority is the same, the router with higher IP address will be elected as the DIS.
- B. When a DIS fails, the backup DIS will take over.
- C. The IS-IS router with the highest priority in the whole broadcast network will be elected as the DIS.
- D. DIS election is configured manually.

Correct Answer: ABC

[H31-124 V2.0 PDF Dumps](#) [H31-124 V2.0 Practice Test](#) [H31-124 V2.0 Braindumps](#)