



# H31-611<sup>Q&As</sup>

HCNA - SDN(Huawei Certified Network Associate - SDN)

## Pass Huawei H31-611 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/h31-611.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which of the following statements are true about OpenFlow interface information reporting? (Choose all that apply.)

- A. After the OpenFlow channel is successfully established, the controller actively queries port information from FPs.
- B. The controller sends Multipart Request messages to query port information.
- C. FPs respond with a Multipart Reply message for batch delivery of port information.
- D. When a port changes, the corresponding FP actively sends a Flow Mod message to report the port change information.

Correct Answer: AB

Reference: <https://support.huawei.com/enterprise/en/doc/EDOC1000102491?section=k007>

---

**QUESTION 2**

Regarding the VS technology of CE series switches on an SDN network, which of the following statements are true? (Choose all that apply.)

- A. All ports on a forwarding chip of the LPU must be allocated to the VS in Group mode at the same time.
- B. All ports on a forwarding chip of the LPU must be allocated to the VS in Port mode at the same time.
- C. Any LPU ports can be freely assigned at any VS in Group mode.
- D. Any LPU ports can be freely assigned at any VS in Port mode.

Correct Answer: AD

Reference: <https://forum.huawei.com/enterprise/en/cloudengine-series-switches-faqs-4-3-vs/thread/420793-861>

---

**QUESTION 3**

Which of the following are parts of the SNMP network management model? (Choose all that apply.)

- A. NMS
- B. Agent
- C. SOA
- D. MIB

Correct Answer: ABD

---

**QUESTION 4**



In BGP, which of the following are methods for loop avoidance?

- A. The Origin attribute of a route records the source from which the route was imported
- B. In a route's AS-Path attribute, all Ass along the path are recorded.
- C. In the next-hop attribute of a route, the route's next hop is recorded.
- D. The MED attribute of a route affects the outbound interface selection of another AS.

Correct Answer: C

---

#### QUESTION 5

Regarding the CE series switches on an SDN network, which of the following statements are true about their application in data centers? (Choose all that apply.)

- A. A CE series switch can connect to a server as a TOR.
- B. The network between TORs and core switches must be an ECMP-enabled Layer 3 network.
- C. The network between TORs and core switches must be a Layer 2 network that runs MSTP to prevent loops.
- D. The network between TORs and core switches can be either a Layer 2 or a Layer 3 network.

Correct Answer: AD

[Latest H31-611 Dumps](#)

[H31-611 Practice Test](#)

[H31-611 Exam Questions](#)