



HH0-450^{Q&As}

Hitachi Data Systems Storage Architect-Hitachi NAS Platform

Pass Hitachi HH0-450 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hh0-450.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

You are designing a Hitachi NAS Platform solution to migrate files to a Hitachi Content Platform (HCP). Which configuration method must be used?

- A. Use the connector wizard.
- B. Use the CLI command `xvl-path-add`.
- C. Use the CLI command `external-path-add`.
- D. Use the CLI command `migration-add-external-path`.

Correct Answer: D

QUESTION 2

You are discussing Fibre Channel (FC) connectivity requirements with a customer who is comparing the capabilities of the different Hitachi NAS Platform models. Which model has a minimum connectivity requirement of 4 FC ports?

- A. 2200
- B. 3080
- C. 3100
- D. 3200

Correct Answer: D

QUESTION 3

When de-migrating files with Data Migrator from Tier 2 back to Tier 1 and there is insufficient space available for the de-migration path, what happens to the de-migration instance?

- A. Data Migrator will look for an alternate location with available space.
- B. Data Migrator will fail the reverse migration instance.
- C. Data Migrator will automatically map to another file system.
- D. Data Migrator will automatically delete data in place of the stub.

Correct Answer: B

QUESTION 4

A customer must have 24/7 uptime on their Hitachi NAS Platform 4-node 3200 cluster. They need to complete a major upgrade on each of the 4 nodes and must have a method of failing over their production services to a non-production



cluster. Which two topics must be discussed with the customer prior to the major upgrade? (Choose two.)

- A. automatic failover using HiTrack
- B. the purchase of a backup cluster
- C. establishing a Server Farm
- D. use of MPIO for failover

Correct Answer: BC

QUESTION 5

A customer wants to install the two nodes of a Hitachi NAS Platform cluster 125 meters apart. What are two prerequisites? (Choose two.)

- A. The cluster interconnect XFPs must be longwave laser extended.
- B. The multimode fiber optic media must comply with the OM3 standard.
- C. A DWDM is required.
- D. The SMU containing the Quorum must have network access to both nodes.

Correct Answer: BD

[Latest HH0-450 Dumps](#)

[HH0-450 Exam Questions](#)

[HH0-450 Braindumps](#)