



HP0-S42^{Q&As}

Architecting HP Server Solutions

Pass HP HP0-S42 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hp0-s42.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is a limitation when configuring a server hardware solution using UDIMMs?

- A. minimum amount of CPUs per channel
- B. maximum size of DIMMs per channel
- C. maximum number of DIMMs per channel
- D. minimum speed of DIMMS per channel

Correct Answer: C

QUESTION 2

What are the power requirements for an HP Apollo 8000 system?

- A. three-phase high voltage AC power input
- B. DC power input
- C. three-stage power rectification
- D. single-phase high voltage AC power input

Correct Answer: A

Reference:

http://www.hp.com/hpinfo/newsroom/press_kits/2014/ComputeEra/HP_Apollo8000System_DataSheet.pdf

QUESTION 3

A customer needs parallel data processing scalability for their custom financial analysis application. Which solution best meets the customer's needs?

- A. a collection of tower servers
- B. high-performance technical cluster
- C. a rack of 1U servers
- D. a collection of blade servers

Correct Answer: B

QUESTION 4



You are discussing a new c7000 BladeSystem solution with your customer and they indicate a possible future need to increase the amount of NICs per server to a total of eight. Which interconnect type fulfills this requirement by using two interconnect bays?

- A. HP 1/10 Gb-F Virtual Connect Ethernet module
- B. Cisco Catalyst Blade Switch 3120X for HP
- C. HP 1/10 Gb Ethernet BL-c Switch
- D. HP Virtual Connect Flex-10 10 Gb Ethernet module

Correct Answer: D

Reference: http://h18004.www1.hp.com/products/quickspecs/13127_div/13127_div.pdf

QUESTION 5

Which column in the exhibit indicates the status of firmware inventory of the managed systems?

HS	MP	SW	VM	PF	ES	System Name	System Type	System Address	Product Name
<input type="checkbox"/>						bl46-240 in End. R133c4	Server	192.168.172.196	ProLiant BL460c G1
<input type="checkbox"/>						bl46-241 in End. R133c4	Server	192.168.172.197	ProLiant BL460c G1

- A. PF
- B. ES
- C. SW
- D. HS

Correct Answer: C