

HP0-Y49^{Q&As}

HP ATP FlexNetwork Solutions

Pass HP HP0-Y49 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass4itsure.com/HP0-Y49.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



VCE & PDF Pass4itSure.com

https://www.pass4itsure.com/HP0-Y49.html 2022 Latest pass4itsure HP0-Y49 PDF and VCE dumps Download

QUESTION 1

A network administrator executes these commands on an HP Comware switch:

[Comware] super password level 1 simple hp1 [Comware] super password level 2 simple hp2 [Comware] super password level 3 simple hp3 [Comware] quit

The network administrator then executes this command to test the configuration:

super 0

What is the outcome of the configuration?

- A. The network administrator is immediately placed into Monitor view.
- B. Access is denied because no level 0 password has been defined.
- C. A password of hp0 must be entered to access the view.
- D. The network administrator is immediately placed into visitor view.

Correct Answer: D

QUESTION 2

When LLDP is enabled, which value is presented by default as the LLDP Chassis ID on both ProVision and Comware switches?

- A. Router ID
- B. System Name
- C. IP address
- D. MAC address

Correct Answer: D

display Ildp local-information Global LLDP local-information: Chassis ID: 00e0-fc00-5600 System name: Sysname System description: H3C Comware Software. H3C S12508 Product Version S12500-C MW710B01BBIT25. Copyright (c) 2004-2011 Hangzhou H3C Tec h. Co., Ltd. All rights reserved. System capabilities supported: Bridge, Router System capabilities enabled: Bridge, Router

MED information: Device class: Connectivity device MED inventory information of master board: HardwareRev: REV.A FirmwareRev: 109 SoftwareRev: 5.20 Alpha 2101 SerialNum: NONE Manufacturer name: H3C Model name: H3C Comware Asset tracking identifier: Unknown Table 1 Command output Field Description Global LLDP local-information Global LLDP information to be sent. Chassis ID Bridge MAC address of the device.

 $Reference: http://www.h3c.com/portal/Technical_Support__Documents/Technical_Documents/Switches/H 3C_S12500_Series_Switches/Command/Command/H3C_S12500_CR-Release71286W710/04/201301/772500_1285_0.htm$

VCE & PDF Pass4itSure.com

https://www.pass4itsure.com/HP0-Y49.html

2022 Latest pass4itsure HP0-Y49 PDF and VCE dumps Download

QUESTION 3

Which STP protection feature does HP recommended against rogue switches?

- A. Root Protection should be enabled on access layer switches.
- B. BPDU Protection should be enabled on edge ports and uplink ports.
- C. Root Protection should be enabled on access and aggregation layer switches.
- D. BPDU Protection should be enabled on edge ports.

Correct Answer: D

We want to enable BPDU protection on any "edge ports", or ports that are connected to end user devices (PCs, printers, etc.) -- any device that should not be sending out STP BPDU\\'s. Without BPDU protection, a malicious (or ignorant) user could plug a switch into our network and alter the spanning tree topology.

QUESTION 4

Which open standard allows a switch with PoE support to correctly determine the power requirements of a connected device?

- A. ICMP
- B. AutoPower
- C. LLDP-MED
- D. CDP

Correct Answer: C

The Link Layer Discovery Protocol (LLDP) is a vendor-neutral link layer protocol in the Internet Protocol Suite used by network devices for advertising their identity, capabilities, and neighbors on an IEEE 802 local area network, principally wired Ethernet. Media Endpoint Discovery is an enhancement of LLDP, known as LLDP-MED, that provides the following facilities:

Auto-discovery of LAN policies (such as VLAN, Layer 2 Priority and Differentiated services settings) enabling plug and play networking. Device location discovery to allow creation of location databases and, in the case of Voice over Internet Protocol (VoIP), Enhanced 911 services. Extended and automated power management of Power over Ethernet (PoE) end points.

QUESTION 5

Which HP ProVision switch command could a network administrator use to upgrade the operating system from an attached USB drive?

- A. Update from usb flash
- B. Copy usb flash



https://www.pass4itsure.com/HP0-Y49.html 2022 Latest pass4itsure HP0-Y49 PDF and VCE dumps Download

C. File-management usb

D. Upgrade usb flash

Correct Answer: B

HP0-Y49 Practice Test

HP0-Y49 Study Guide HP0-Y49 Exam Questions



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.pass4itsure.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4itsure, All Rights Reserved.