



HP0-Y52^{Q&As}

Applying HP FlexNetwork Fundamentals

Pass HP HP0-Y52 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hp0-y52.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Refer to the exhibits.

Exhibit 1

```
Switch-C# show vlan 1
Status and Counters - VLAN Information - VLAN 1
VLAN ID : 1
Name : VLAN1
Status : Port-based
Voice : No
Jumbo : No

Port Information   Mode           Unknown VLAN   Status
-----
1                 Untagged      Learn          Up
2                 Untagged      Learn          Up
```

Exhibit 2

```
Switch-C# show vlan 2
Status and Counters - VLAN Information - VLAN 2
VLAN ID : 2
Name : VLAN2
Status : Port-based
Voice : No
Jumbo : No

Port Information   Mode           Unknown VLAN   Status
-----
1                 Tagged        Learn          Up
2                 Tagged        Learn          Up
```

A network administrator executes the show vlan commands and sees the output shown in the exhibits. How must the administrator configure a connected port on an HP Comware switch?

- A. as a trunk port
- B. as an access port
- C. as an untagged port
- D. as a mixed port

Correct Answer: A

QUESTION 2

Which HP solution delivers automated virtual machine orchestrator, automatic synchronization of network connectivity information, and visibility to performance of wired and wireless users?



- A. Unified Wired-WLAN modules and switches
- B. Intelligent Management Center (IMC)
- C. Virtual Connect FlexFabric
- D. Intelligent Resilient Framework

Correct Answer: B

QUESTION 3

A company requires switches to use Multiple Spanning Tree Protocol (MSTP) instead of Rapid Spanning Tree Protocol (RSTP), so that the switches can forward traffic on more than one switch-to-switch link. How does the administrator set up the solution to meet this requirement?

- A. Configure every switch with a unique bridge priority in the IST, which is also called spanning tree instance 0.
- B. Ensure that switches use the 802.3t standard costs instead of the legacy costs.
- C. Set the same spanning tree cost on all redundant links on a switch.
- D. M different VLANs to different instances, and make a different switch root bridge in each instance.

Correct Answer: D

QUESTION 4

What is one difference between Network Segment-based discovery and ARP-based discovery on HP Intelligent Management Center (IMC)?

- A. With Network Segment-based discovery, IMC can discover multiple devices. With ARP- based discovery, IMC can only discover one device; the administrator must re-run ARP- based discovery to discover a second device.
- B. With Network Segment-based discovery, network device login settings must match login settings on IMC. With ARP-based discovery, only ARP settings must match.
- C. With Network Segment-based discovery, network device SNMP settings must match SNMP settings on IMC. With ARP-based discovery, only ARP settings must match.
- D. With Network Segment-based discovery, the administrator enters a range of IP addresses to discover. With ARP-based discovery, the administrator enters one seed IP address, and IMC dynamically learns more IP addresses to discover.

Correct Answer: D

QUESTION 5



A network administrator adds a new VLAN in a campus network, VLAN 120. The administrator needs to set up a DHCP scope for this VLAN. The scope will include an IP address for DHCP clients and a default gateway address. An HP Comware aggregation layer switch acts as a DHCP server for this VLANs at the access layer. The administrator configures this on the Comware switch for the new DHCP scope:

```
dhcp server ip-pool 120
  network 10.1.120.0 24
  gateway 10.1.120.254
  expired 1 day
  quit
dhcp server forbidden-ip 10.1.120.250 10.1.120.254
dhcp server ping packets 2
dhcp server ping timeout 750
```

Based on this configuration, what else must the administrator configure to make the pool available to DHCP clients that send requests in VLAN 120?

- A. dhcp vlan 120
- B. dhcp server ip pool 120vlan 120
- C. dhcp enable
- D. dhcp server vlan 120

Correct Answer: C

[Latest HP0-Y52 Dumps](#)

[HP0-Y52 PDF Dumps](#)

[HP0-Y52 Brindumps](#)