



# HP2-Z30<sup>Q&As</sup>

Fast Track - Applying HP FlexNetwork Fundamentals

## Pass HP HP2-Z30 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hp2-z30.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Which HP switch supports nine switches in an IRF topology?

- A. 5120-SI
- B. 5820
- C. 7500
- D. 12500

Correct Answer: B

---

**QUESTION 2**

What are the default logging properties for an HP Comware switch? (Select two)

- A. Displays debugging output to the console
- B. Displays log messages to the console
- C. Uses the Information Center to control logging functions
- D. Uses the Event Log to save log messages
- E. Supports five logging levels

Correct Answer: BC

---

**QUESTION 3**

Which action can be performed from an HP Comware switch?

- A. Execute the super command to change privilege levels.
- B. Execute the startup-default command to define the configuration file to load upon bootup.
- C. Execute the show flash command to examine the operating systems stored in flash.
- D. Execute the boot set-default flash command to define the default operating system to load.

Correct Answer: A

---

**QUESTION 4**

Refer to the HP Comware configuration. interface vlan 1 ip address 10.1.1.1 255.255.255.0 quit interface vlan 2 ip address 10.1.2.1 255.255.255.0 quit interface loopback 1



ip address 1.1.1.1 255.255.255.255 quit router-id 1.1.1.1 area 0 network 1.0.0.0 0.255.255.255 network 10.1.1.0 0.255.255.255 The network administrator set up VLAN 2 as a management VLAN. This VLAN should not be included in the OSPF routing process. Now only directly connected network administrators in VLAN 2 can manage the switch. How should the network administrator solve this problem?

- A. Define the management-vlan 2 command.
- B. Change the network command in OSPF.
- C. Define the VLAN 2 interface as a silent interface.
- D. Define the ip authorized-managers 10.1.0.0/24 command.

Correct Answer: C

---

### QUESTION 5

A network administrator has an HP Comware switch that is configured with OSPF. The network administrator views the routing table and sees that a default route was learned from an OSPF neighbor (10.1.1.1). However, the network administrator wants to override this action and use a different neighbor (10.1.1.2) for the default route.

The network administrator configures this command:

```
[Comware] ip route-static 0.0.0.0 0 10.1.1.2
```

After configuring the command, the network administrator examines the routing table and notices that the original neighbor's default route is still in the routing table, but the static route is missing.

What is the cause of this problem?

- A. OSPF routes have a lower precedence value
- B. The ip default-gateway command must be used when creating a default route
- C. Only one routing protocol can be operational on a Comware device
- D. The static route has a syntax mistake

Correct Answer: A

[HP2-Z30 Practice Test](#)

[HP2-Z30 Study Guide](#)

[HP2-Z30 Braindumps](#)