



HP2-Z30^{Q&As}

Fast Track - Applying HP FlexNetwork Fundamentals

Pass HP HP2-Z30 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hp2-z30.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which task should a network administrator include in the creation of an upgrade policy?

- A. Update network management software before deploying upgrades to network switches.
- B. Make a copy of the original operating system.
- C. Test the upgrade on a core switch.
- D. Read the release notes of the original operating system.

Correct Answer: B

QUESTION 2

Which Access Point (AP) type corresponds to HP MSM autonomous operational mode?

- A. Thin
- B. Fat
- C. Modal
- D. Fit

Correct Answer: B

QUESTION 3

A network administrator has created and applied a configuration to an HP Provision switch. The network administrator then copied the active configuration to a TFTP server. Upon examining the configuration file on the TFTP server, the network administrator noticed that the operator and manager passwords were not in the saved configuration file.

Which command must the network administrator execute to accomplish this task?

- A. include-credentials
- B. include-passwords
- C. save-credentials
- D. backup-accounts

Correct Answer: A

QUESTION 4

A network administrator receives a new HP Provision switch and notices that the software version running on the switch



is older than what is currently used in the network. The network administrator copies an updated version of the operating

system from the new switch's USB port to the secondary flash location. The network administrator then executes the following command:

Provision# boot system flash secondary:

The switch reboots using the new operating system. However, when the network administrator turns off the switch and turns it back on, the switch boots from the old operating system.

Which solution should the network administrator use to fix the problem?

- A. Execute the startup-boot secondary command.
- B. Boot into the switch's Monitor ROM Console and perform the upgrade a second time.
- C. Execute the boot set-default flash secondary command.
- D. Execute the boot-loader file command.
- E. Execute the startup-default secondary command.

Correct Answer: C

Explanation: <http://hpblogs.lithium.com/t5/HP-Networking/HP-ProCurve-using-multiple-config-files/ba-p/42024#.Uy-5LqiSwkQ>

QUESTION 5

A network administrator executes the following command:

```
[Comware-1] display brief interface
The brief information of interface(s) under route mode:
Interface          Link      Protocol-link  Protocol type  Main IP
NULL0              UP        UP(spoofing)  NULL           --
Vlan1              DOWN     DOWN          ETHERNET       10.1.1.1
Vlan2              UP        UP            ETHERNET       10.2.2.1
<-output omitted->
```

What is the state of the VLAN 1 interface?

- A. All interfaces in VLAN 1 are down.
- B. The IP address of VLAN 1 conflicts with another device in VLAN 1.
- C. The IP address for VLAN 1 is a duplicate of another VLAN interface on the switch.
- D. VLAN 1 has a single port in a down state.

Correct Answer: D



VCE & PDF

Pass4itSure.com

<https://www.pass4itsure.com/hp2-z30.html>

2024 Latest pass4itsure HP2-Z30 PDF and VCE dumps Download

[Latest HP2-Z30 Dumps](#)

[HP2-Z30 Practice Test](#)

[HP2-Z30 Study Guide](#)