



# HP2-Z33<sup>Q&As</sup>

HP Unified Wired-Wireless Networks and BYOD

## Pass HP HP2-Z33 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hp2-z33.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

When accessing the wireless network in 802.1X with EAP-TLS, what do the user endpoints require?

- A. username and password of the user's account
- B. client certificate or root certificate
- C. client certificate and root certificate
- D. MS-CHAPV2 to be configured

Correct Answer: C

Reference: [http://technet.microsoft.com/en?/s/library/cc739638\(v=ws.10\).aspxv](http://technet.microsoft.com/en?/s/library/cc739638(v=ws.10).aspxv).

---

### QUESTION 2

A research company wants to deploy a high throughput 802.11n only wireless network. The network administrator selects the "client dot11n-only" option. Which other configuration option must the network administrator configure?

- A. maximum MCS index
- B. basic rate 6Mb/s
- C. mandatory rates MCS0-MCS15
- D. MCS15 data rate

Correct Answer: A

Configuring 802.11n Rates

Introduction to MCS

Configuration of mandatory and supported 802.11n rates is achieved by specifying the maximum Modulation and Coding Scheme (MCS) index. The MCS data rate table shows relations between data rates, MCS indexes, and parameters that

affect data rates. A sample MCS data rate table in the 20 MHz mode is shown in Table 1-4. For the whole table, refer to IEEE P802.11n D2.00.

Table 1-4 MCS data rate table (20 MHz)

---

### QUESTION 3

Where can a network administrator check for successful authentication in User Access Manager?

- A. User Access Log > Auth Failure Log
- B. User Access > LDAP Users



- C. User Access Log > Access Details
- D. User Access > Access Device Log

Correct Answer: C

---

#### QUESTION 4

A customer is planning to deploy HP MSM466-R access points in an extreme cold environment to interconnect to the Unified Wired-WLAN Module in the HP switch. Which requirement is needed to accomplish this?

- A. NEMA 4X enclosures should be used to house the access points.
- B. Switch ports must support PoE.
- C. PoE redundancy must be enabled on the interface.
- D. Access Point must deploy internal antennas.

Correct Answer: B

---

#### QUESTION 5

The Wireless Intrusion Prevention System (WIPS) determines that a client has exceeded the maximum number of authentication requests that a client should make in the allowed period. What does the WIPS system do?

- A. adds the client's MAC address to the static blacklist on the access controller
- B. adds the client's MAC address to the static blacklist on the access point
- C. adds the client's MAC address to the dynamic blacklist for the access point
- D. removes the client's MAC address from the whitelist on the access controller

Correct Answer: C

[HP2-Z33 PDF Dumps](#)

[HP2-Z33 Practice Test](#)

[HP2-Z33 Braindumps](#)