



# HPE2-T34<sup>Q&As</sup>

Using HPE OneView

**Pass HP HPE2-T34 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hpe2-t34.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

Before applying server profiles to a group of servers. What is the first thing you should check?

- A. The servers are powered down.
- B. The servers have the correct firmware installed.
- C. The servers are all Synergy compute modules.
- D. The servers are all the same server hardware type.

Correct Answer: D

---

### QUESTION 2

Which parameter does the server profile assign to a Flex-10 adapter in a blade server profile?

- A. MAC address
- B. Hardware iSCSI initiator name
- C. WWN
- D. iLO IP address

Correct Answer: A

---

### QUESTION 3

What public resource is available to help administrators who want to automate operations by using the PowerShell interface to the HPE OneView REST API and the Synergy Composable API?

- A. HPE OneView server templates
- B. GitHub library
- C. HPE Support Center
- D. HPE Software Depot

Correct Answer: C

Reference: [https://support.hpe.com/hpsc/doc/public/display?docId=emr\\_na-a00037747en\\_usanddocLocale=en\\_US](https://support.hpe.com/hpsc/doc/public/display?docId=emr_na-a00037747en_usanddocLocale=en_US)

---

### QUESTION 4

HOTSPOT



A customer has a four node ESXi cluster. They update drivers via vCenter Update Manager and want use HPE OneView Server Profile Templates to update the firmware while the systems are online. Click on the place they should select within the server profile template to update the firmware while the systems are online.

Hot Area:

**Edit**    **ESXi on BL460c Gen9**    **Server Profile** ▾

---

**Server Profile**

**Firmware**

Firmware baseline

Installation Method

Activate firmware

Service Pack for ProLiant version 2017.04.0 ▾

☐ Force installation

☐ Firmware and OS Drivers using Smart Update Tools

☐ Firmware only using Smart Update Tools

☐ Firmware only

☐ Immediately   ☐ At a scheduled date and time   ☐ Not scheduled

*Changed: Firmware baseline to "Service Pack for ProLiant version 2017.04.0"*

OK

Cancel

Correct Answer:



**Edit**    ESXi on BL460c Gen9    Server Profile ▾

---

**Server Profile**

**Firmware**

Firmware baseline

Service Pack for ProLiant version 2017.04.0 ▾

☐ Force installation

Installation Method

☐ Firmware and OS Drivers using Smart Update Tools

☒ Firmware only using Smart Update Tools

☐ Firmware only

Activate firmware

☐ Immediately   ☐ At a scheduled date and time   ☐ Not scheduled

---

*Changed: Firmware baseline to "Service Pack for ProLiant version 2017.04.0"*

OK

Cancel

**QUESTION 5**

What must be disabled when strict two-factor authentication is enabled?

- A. emergency local login
- B. SSL certificates
- C. local login
- D. REST API

Correct Answer: B

[HPE2-T34 VCE Dumps](#)

[HPE2-T34 Practice Test](#)

[HPE2-T34 Study Guide](#)