



# HPE2-Z40<sup>Q&As</sup>

Delta - Applying Aruba Switching Fundamentals for Mobility

## Pass HP HPE2-Z40 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hpe2-z40.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



**QUESTION 1**

A network administrator wants to form a cluster with several Aruba Instant APs (IAPs). What must the administrator verify?

- A. that all APs are pre-configured with WLANs with the same SSID
- B. that all APs are operating on the same radio channel
- C. that all APs are the same model
- D. that all APs are connected in the same subnet

Correct Answer: A

---

**QUESTION 2**

A network administrator configures LLDP-MAD on an Aruba Virtual Switching Framework (VSF) fabric. The administrator needs to enter an SNMP community string after v2c in this command: Switch(config)# vsf lldp-mad ipv4 10.1.0.2 v2c

Which SNMP community string should the administrator enter?

- A. one configured for the VSF fabric on AirWave.
- B. one configured on the device at 10.1.0.2.
- C. one configured on the standby member in the fabric.
- D. one configured on the VSF fabric as a whole.

Correct Answer: C

---

**QUESTION 3**

A network administrator needs to reach an ArubaOS switch CU at a management IP address. The administrator also needs to ensure that the switch entirely rejects Telnet and SSH connections from users in data VLANs.

How can the administrator meet these goals?

- A. Configure the management IP address on the default VLAN and set a manager password.
- B. Configure the management IP address on a VTY interface and bind an ACL to this interface.
- C. Configure the management IP address on any VLAN except the default VLAN. Set a manager and operator password.
- D. Configure the management IP address on the OOBM port and configure the switch to listen for Telnet and SSH only on this port.



Correct Answer: D

#### QUESTION 4

Refer to the exhibit.

The screenshot shows the 'New WLAN' configuration interface. The 'VLAN' tab is active. Under 'Client IP & VLAN Assignment', the 'Client IP assignment' is set to 'Network assigned' (selected with a radio button). The 'Client VLAN assignment' is set to 'Default' (selected with a radio button). Other options include 'Virtual Controller managed', 'Static', and 'Dynamic'.

The exhibit shows settings for a WLAN on an Aruba Instant cluster. To which VLAN is wireless user traffic assigned?

- A. to the untagged VLAN on switch ports connected to the Instant APs
- B. to the VLAN defined for wireless users in Aruba AirWave
- C. to the default VLAN defined in the System settings in the Instant
- D. to the default VLAN on switches connected to the Instant APs

Correct Answer: D

#### QUESTION 5

An ArubaOS switch has no passwords or user accounts configured on it. A network administrator then enters these commands: Switch(config)# password manager user-name admin1 plaintext mysecret1 Switch(config)# password manager user-name admin2 plaintext mysecret2 Switch(config)# aaa authentication local-user admin3 group Level-15 Password plaintext New password for admin3: hpe Please retype new password for admin3: hpe Which users can access the switch CU and use enable and global configuration commands?

- A. Admin1 and admin2
- B. admin2 and admin3
- C. admin1 and admin3
- D. admin1 admin2, and admin3

Correct Answer: C