



HPE6-A42^{Q&As}

Implementing Aruba WLAN (IAW) 8

Pass HP HPE6-A42 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hpe6-a42.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

A network administrator adds several new APs to an Aruba solution that uses AirMatch. The administrator does not want to change the channel for the existing APs, but wants the new APs to receive a provisional plan for their channels and power.

What should the administrator do to meet this goal?

- A. Run an on-demand quick AirMatch optimization.
- B. Run an on-demand incremental AirMatch optimization.
- C. Temporarily enable ARM on the existing and new APs, while AirMatch scheduling remains enabled.
- D. Temporarily disable AirMatch scheduling, and then enable ARM on the existing and new APs.

Correct Answer: B

QUESTION 2

A network administrator uses a wireless intrusion detection system (WIDS) to detect 802.11 association floods. At which layer do these attacks occur?

- A. Layer 1
- B. Layer 2
- C. Layer 3
- D. Layer 7

Correct Answer: B

QUESTION 3

A network administrator configures this policy:

```
ip access-list session Guest
  user any svc-dhcp permit
  user any network 10.0.0.0 255.0.0.0 deny
  user any any permit
```

Users to which this policy applies are unable to receive IP addresses with DHCP. How should the administrator fix the issue?

- A. Change user to any in the user any svc-dhcp permit rule.
- B. Move the user any svc-dhcp permit rule to the bottom of the list.



- C. Remove the deny rule from the policy.
- D. Use the correct service alias in the user any svc-dhcp permit rule.

Correct Answer: D

QUESTION 4

A company currently uses Instant APs (IAPs), all managed by a virtual controller. The company expects to double in size without the next 18 months. The network manager wants to purchase additional APs to service the increased traffic load. The network manager also wants to deploy a Mobility Controller (MC) to manage all APs.

How should the network administrator adapt the current IAPs to a controlled architecture?

- A. Manage both the MCs and IAP clusters with Aruba Central.
- B. Configure the IAPs to establish CPSec tunnels to the new MCs.
- C. Manage both the MCs and IAP clusters with a Mobility Master (MM).
- D. Convert the IAPs to Campus APs controlled by the new MCs.

Correct Answer: B

QUESTION 5

A company wants to provide wireless access for guests with their Aruba solution. Which configuration feature requires the customer to purchase PEFNG licenses?

- A. redirection of guests to an external captive portal
- B. provision of DHCP services to unauthenticated guests
- C. addition of custom rules to control access for authenticated guests
- D. customization of the internal captive portal login page

Correct Answer: C

[HPE6-A42 PDF Dumps](#)

[HPE6-A42 Practice Test](#)

[HPE6-A42 Braindumps](#)