



HPE6-A42^{Q&As}

Implementing Aruba WLAN (IAW) 8

Pass HP HPE6-A42 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hpe6-a42.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

A customer has a large campus that requires 400 Aruba 335 APs to support a total of 10,000 wireless users and 12Gbps of traffic. Although the customer wants two controllers for redundancy, each controller must be able to support all of the APs and users on its own.

Which Aruba Mobility Controller models meet the customer requirements and DO NOT unnecessarily exceed them?

- A. Aruba 7024 controllers
- B. Aruba 7210 controllers
- C. Aruba 7240 controllers D. Aruba 7030 controllers

Correct Answer: B

QUESTION 2

Refer to the exhibits. Exhibit 1

Roles>users1

GLOBAL RULES

+

RULES FOR THIS ROLE ONLY

- ◇ permit all from source any to alias network1
- ◇ deny all from source any to network 172.16.0.0/255.255.0.0
- ◇ permit all from source user to any destinations

Exhibit 2

**Roles Policies Applications**

Roles > users2

[Show Advanced View](#)**GLOBAL RULES****RULES FOR THIS ROLE ONLY**

- ☐ permit all from source user to network 10.1.1.0/255.255.255.0
- ☐ deny all from source user to network 10.1.2.0/255.255.255.0
- ☐ permit all from source user to network 10.1.0.0/255.255.0.0

A company has an Aruba solution. Client 1 is assigned to the users1 role, and client 2 is assigned to the users2 role. The exhibits show current firewall rules for those roles. The network1 alias used to be 10.1.1.0/24, but the network administrator now changes the network1 alias to 172.16.1.0/24. Client 1 and Client 2 both send a packet destined to 172.16.1.10.

How does the firewall handle these packets?

- A. It permits the packet from Client 1 and denies the packet from Client 2.
- B. It permits both packets.
- C. It denies the packet from Client 1 and permits the packet from Client 2.
- D. It denies both packets.

Correct Answer: A

QUESTION 3

What is a reason for a company to choose to deploy an Aruba 7024 Mobility Controller (MC) rather than an Aruba 7010 MC?

- A. to support 802.11ac Aps rather than only 802.11n APs
- B. to support more wireless users



C. to support more POE devices directly connected to the MC

D. to support a faster firewall throughput rate

Correct Answer: C

QUESTION 4

A company has an Aruba Mobility Master (MM)-based solution. Under which circumstance will an AP radio change channel without the use of the Mobility Master (MM)?

A. when the MM detects that a different channel has significantly better quality

B. when the Mobility Controller (MC) detects a rogue AP on the channel

C. when the AP detects a large amount of interference on its channel

D. when the Client Match rules indicate that nearby clients do not support the current channel

Correct Answer: C

QUESTION 5

A network administrator adds several new APs to an Aruba solution that uses AirMatch. The administrator does not want to change the channel for the existing APs, but wants the new APs to receive a provisional plan for their channels and power.

What should the administrator do to meet this goal?

A. Run an on-demand quick AirMatch optimization.

B. Run an on-demand incremental AirMatch optimization.

C. Temporarily enable ARM on the existing and new APs, while AirMatch scheduling remains enabled.

D. Temporarily disable AirMatch scheduling, and then enable ARM on the existing and new APs.

Correct Answer: B

[Latest HPE6-A42 Dumps](#)

[HPE6-A42 PDF Dumps](#)

[HPE6-A42 Study Guide](#)