



JN0-130^{Q&As}

Juniper networks Certified internet specialist.e(jncis-e)

Pass Juniper JN0-130 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-130.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



**QUESTION 1**

In a Bridged 1483 network, which CLI commands are used to baseline an IP interface on ATM 6/1.1 and display recent IP transmit and receive statistics?

- A. clear ip interface atm 6/1.1 show ip interface atm 6/1.1
- B. baseline atm interface atm 6/1.1 show ip interface atm 6/1.1
- C. clear ip interface atm 6/1.1 show ip interface atm 6/1.1 delta
- D. baseline atm interface atm 6/1.1 show ip interface atm 6/1.1 delta

Correct Answer: D

QUESTION 2

You are running OSPF between two ERX Edge Routers across an OC-12c link with HDLC encapsulation. How many designated routers are present for this link?

- A. 0
- B. 1
- C. 2
- D. 3

Correct Answer: A

QUESTION 3

What describes the functionality of NTP when using multiple virtual routers?

- A. All virtual routers can act as NTP clients and servers.
- B. Only one virtual router can act as an NTP client and a server.
- C. Only one virtual router can act as an NTP server but all can be clients.
- D. Only one virtual router can act as an NTP client but all can be servers.

Correct Answer: D

QUESTION 4

An ATM PVC is configured as atm pvc 1 0 101 aal5snap 256 128 100. Which three statements describe the traffic management characteristics of this interface? (Choose three.)



- A. The burst size is 128 cells.
- B. The burst size is 100 cells.
- C. This is a real-time variable service.
- D. The peak rate is 256K bits per second.
- E. This is a non-real-time variable service.

Correct Answer: BDE

QUESTION 5

A Bridged 1483 network is grouping all DSL users into a single logical subnet. Which configuration command prevents the end users from directly communicating with each other?

- A. no ip arp
- B. no ip proxy-arp
- C. restrict ip arp
- D. restrict ip proxy-arp

Correct Answer: B

[JN0-130 Practice Test](#)

[JN0-130 Study Guide](#)

[JN0-130 Braindumps](#)