



JN0-1302^{Q&As}

Data Center Design Specialist (JNCDS-DC)

Pass Juniper JN0-1302 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-1302.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which statement about a Virtual Chassis deployment is correct?

- A. A Virtual Chassis can include switches mounted in multiple different racks.
- B. A Virtual Chassis can interconnect as many as 20 switches to form a single virtual device.
- C. A Virtual Chassis uses Spanning Tree Protocol between individual member switches.
- D. All member switches must be running the same Junos version.

Correct Answer: D

QUESTION 2

You are performing a risk assessment on your new data center. You must determine the annual loss expectancy.

Which two calculations must you use in this scenario? (Choose two.)

- A. single loss expectancy
- B. asset value
- C. annual rate of occurrence
- D. exposure factor

Correct Answer: AB

QUESTION 3

You want to reduce the over-subscription ratio of an IP fabric between the leaf nodes and spine nodes. Which two actions will accomplish this goal? (Choose two.)

- A. Add spine nodes to the fabric.
- B. Increase bandwidth between the spine and leaf.
- C. Add leaf nodes to the fabric.
- D. Add aggregate links to the servers.

Correct Answer: AB

QUESTION 4

Which three statements about Contrail Networking are true? (Choose three.)



- A. It is used to service chain network functions.
- B. It is used to program physical network functions.
- C. It is used to virtualize and program networks.
- D. It is used to virtualize and program compute.
- E. It is used to create distributed cloud storage.

Correct Answer: ACE

QUESTION 5

What are two considerations when designing an IP fabric? (Choose two.)

- A. Every leaf node should have an uplink to every spine node.
- B. Leaf nodes and spine nodes should be the same type of device.
- C. Uplinks from servers to the leaf nodes should be 40GbE links.
- D. All spine nodes should be the same type of device.

Correct Answer: AC

[JN0-1302 Practice Test](#)

[JN0-1302 Study Guide](#)

[JN0-1302 Exam Questions](#)