



JN0-333^{Q&As}

Security, Specialist (JNCIS-SEC)

Pass Juniper JN0-333 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-333.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which interface is used exclusively to forward Ethernet-switching traffic between two chassis cluster nodes?

- A. swfab0
- B. fxp0
- C. fab0
- D. me0

Correct Answer: A

QUESTION 2

Click to the Exhibit button.

Referring to the exhibit, which two statements are true? (Choose two.)

```
[edit]
user@host# show security zones security zones security-zone
trust
host-inbound-traffic {
    system-services {
        all;
    }
}
interfaces {
    ge-0/0/0.0;
    ge-0/0/1.0 {
        host-inbound-traffic {
            system-services {
                ssh;
            }
        }
    }
}
```

- A. Interface ge-0/0/0 will not accept SSH connections.
- B. Interfaces ge-0/0/0.0 and ge-0/0/1.0 will allow SSH connections.
- C. Interface ge-0/0/0.0 will respond to pings.
- D. Interface ge-0/0/1.0 will respond to pings.

Correct Answer: BD



QUESTION 3

You are asked to support source NAT for an application that requires that its original source port not be changed.

Which configuration would satisfy the requirement?

- A. Configure a source NAT rule that references an IP address pool with interface proxy ARP enabled.
- B. Configure the egress interface to source NAT fixed-port status.
- C. Configure a source NAT rule that references an IP address pool with the port no-translation parameter enabled.
- D. Configure a source NAT rule that sets the egress interface to the overload status.

Correct Answer: C

QUESTION 4

Click the Exhibit button.



```
{primary:node0} [edit]
user@host# show chassis cluster
reth-count 2;
control-ports {
  fpc 0 port 0;
  fpc 3 port 0;
}
redundancy-group 0 {
  node 0 priority 200;
  node 1 priority 100;
}
redundancy-group 1 {
  node 0 priority 200;
  node 1 priority 100;
}
ip-monitoring {
  global-weight 150;
  global-threshold 240;
  retry-interval 3;
  retry-count 10;
  family {
    inet {
      172.16.1.100 {
        weight 150;
        interface reth0.0 secondary-ip-address 10.1.1.1;
      }
    }
  }
}
}
{primary:node0} [edit]
user@host# show interfaces
xe-1/0/0 {
  gigether-options {
    redundant-parent reth0;
  }
}
xe-4/0/0 {
  gigether-options {
    redundant-parent reth0;
  }
}
fab0 {
  fabric-options {
    member-interfaces {
      xe-1/1/10;
    }
  }
}
fab1 {
  fabric-options {
    member-interfaces {
      xe-4/1/10;
    }
  }
}
reth0 {
  unit 0 {
    family inet {
      address 10.1.1.1/24;
    }
  }
}
}
```



Which statement would explain why the IP-monitoring feature is functioning incorrectly?

- A. The global weight value is too large for the configured global threshold.
- B. The secondary IP address should be on a different subnet than the reth IP address.
- C. The secondary IP address is the same as the reth IP address.
- D. The monitored IP address is not on the same subnet as the reth IP address.

Correct Answer: C

QUESTION 5

Click the Exhibit button.

```
[edit]
user@host# show security address-book
global {
  address dmz-net 192.168.150.0/24;
  address dns-svrs {
    range-address 192.168.150.100 {
      to {
        192.168.150.115;
      }
    }
  }
  address client-net 172.16.123.0/24;
}

[edit security policies from-zone trust to-zone dmz]
user@host# show
policy p1 {
  match {
    source-address client-net;
    destination-address dns-svrs;
    destination-address-excluded;
    application [ junos-http junos-https ];
  }
  then {
    permit;
  }
}
policy p2 {
  match {
    source-address any;
    destination-address any;
    application any;
  }
  then {
    permit;
  }
}
```



Referring to the exhibit, what will happen if client 172.16.128.50 tries to connect to destination 192.168.150.111 using HTTP?

- A. The client will be denied by policy p2.
- B. The client will be denied by policy p1.
- C. The client will be permitted by policy p2.
- D. The client will be permitted by policy p1.

Correct Answer: D

[JN0-333 VCE Dumps](#)

[JN0-333 Study Guide](#)

[JN0-333 Braindumps](#)