



JN0-348^{Q&As}

Enterprise Routing and Switching, Specialist

Pass Juniper JN0-348 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-348.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

How many bytes of overhead are added to a packet traversing a GRE tunnel?

- A. 20
- B. 24
- C. 12
- D. 16

Correct Answer: B

QUESTION 2

You want to advertise only a default route into a new area, which will be called area 7. In this scenario, which configuration statement would solve this problem?

- A. user@host# set protocols ospf area 0.0.0.7 nssa default-lsa default-metric 10
- B. user@host# set protocols ospf area 0.0.0.7 stub no-summaries
- C. user@host# set protocols ospf area 0.0.0.7 stub default-metric 10
- D. user@host# set protocols ospf area 0.0.0.7 stub

Correct Answer: A

QUESTION 3

Which Junos feature allows you to combine multiple interfaces into a single bundle?

- A. VRRP
- B. Virtual Chassis
- C. LAG
- D. NSB

Correct Answer: C

QUESTION 4

Your network is configured with dynamic ARP inspection (DAI) using the default parameters for all the DHCP and ARP related configurations. You just added a new device connected to a trunk port and configured it to obtain an IP address using DHCP.



Which two statements are correct in this scenario? (Choose two.)

- A. The DHCP server assigns the IP addressing information to the new device.
- B. DAI validates the ARP packets for the new device against the DHCP snooping database.
- C. The ARP request and response packets for the new device will bypass DAI.
- D. DHCP snooping adds the DHCP assigned IP address for the new device to its database.

Correct Answer: AB

QUESTION 5

Click the Exhibit button.



```
[edit protocols bgp]
user@router# show
preference 150;
keep all;
mtu-discovery;
export static-1;
remove-private;
tcp-mss 4096;
group one {
    export static-2;
    peer-as 2;
    neighbor 10.1.0.1 {
        export static-3;
    }
}
group two {
    type internal;
    local-address 192.168.1.11;
    export static-4;
    local-as 1;
    neighbor 192.168.1.12;
    neighbor 192.168.1.13
}
```

Referring to the exhibit, which policy will export routes to IBGP peers?

- A. static-3
- B. static-4
- C. static-1
- D. static-2

Correct Answer: B