



JN0-351^{Q&As}

Enterprise Routing and Switching Specialist (JNCIS-ENT)

Pass Juniper JN0-351 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-351.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

Given the exhibit, which two statements are correct regarding the graceful-restart state for the BGP groups? (Choose two.)



```
[edit]
user@host# show protocols bgp group IBGP
type internal;
local-address 7.7.7.7;
export no-routes-filter;
graceful-restart {
    restart-time 100;
}
neighbor 1.1.1.1 {
    accept-remote-nexthop;
    import fix-nexthop;
    family inet {
        unicast;
    }
    family inet6 {
        unicast;
    }
}
neighbor 2.2.2.2;
[edit]
user@host# show protocols bgp group EBGP
type external;
multipath;
neighbor 198.168.4.2 {
    family inet {
        unicast;
    }
    peer-as 100;
    local-as 15169;
    multipath;
}
neighbor 198.168.5.2 {
    family inet {
        unicast;
    }
    peer-as 100;
    local-as 15169;
    multipath;
}
neighbor 198.168.6.2 {
    family inet {
        unicast;
    }
    peer-as 100;
    local-as 15169;
    multipath;
}
[edit]
user@host# show routing-options graceful-restart
disable;
```



- A. The graceful-restart capability will be enabled for group IBGP.
- B. The graceful-restart capability will be disabled for group IBGP.
- C. The graceful-restart capability will be disabled for group EBGP.
- D. The graceful-restart capability will be enabled for group EBGP.

Correct Answer: AC

QUESTION 2

Click the Exhibit button.

```
{master:0}
user@switch> show spanning-tree bridge
STP bridge parameters
Context ID                : 0
Enabled protocol          : RSTP
  Root ID                 : 8192.50:c5:8d:ae:db:41
  Root cost                : 40000
  Root port               : ge-0/0/14.0
  Hello time              : 2 seconds
  Maximum age             : 40 seconds
  Forward delay           : 30 seconds
  Message age             : 4
  Number of topology changes : 1
  Time since last topology changes : 64 seconds
  Topology change initiator : ge-0/0/14.0
  Topology change last recvd. from : 2c:6b:f5:31:06:0e
Local parameters
  Bridge ID               : 32768.50:c5:8d:ae:bd:41
  Extended system ID      : 0
  Internal instance ID    : 0
```

Referring to the exhibit, which statement is correct?

- A. The device is the root bridge?
- B. The spanning tree session has timed out.
- C. The local bridge priority is set to 8k.
- D. The bridge priority on the root device is set to 8k.

Correct Answer: D



QUESTION 3

Which statement describes GRES?

- A. GRES requires NSR to function properly.
- B. GRES provides routing loop protection.
- C. GRES provides hardware-level high availability.
- D. GRES rapidly detects link failures.

Correct Answer: A

QUESTION 4

Click the Exhibit button.



```
user@host# show interfaces
ge-0/0/0 {
    unit 0{
        family iso;
        family inet {
            address 10.0.24.1/24;
        }
    }
}
ge-0/0/1 {
    unit 0{
        family iso;
        family inet {
            address 10.0.25.1./24;
        }
    }
}
ge-0/0/2 {
    unit 0{
        family iso;
        family inet {
            address 10.0.26.1/24;
        }
    }
}
lo {
    unit 0{
        family inet {
            address 192.168.2.1/32;
        }
    }
}
user@host#show protocols isis
interface ge-0/0/0.0 {
    level 1 disable;
}
interface ge-0/0/1.0 {
    level 2 disable;
}
interface ge-0/0/2.0 {
    level 2 disable;
}
interface lo0 {
    level 2 disable;
}
```



You are attempting to set up IS-IS on a device that has two interfaces (ge-0/0/1.0 and ge-0/0/2.0) in Level 1 and one interface (ge-0/0/0.0) in Level 2; however, it does not participate in either level.

Referring to the exhibit, what is the problem?

- A. The ge-0/0/0.0 interface must have the Level 1 disable statement removed.
- B. The lo0 interface must participate in both levels. . One of the interfaces requires a network entity title on it.
- C. All of the interfaces must have the level disable statement removed.

Correct Answer: C

QUESTION 5

Which two types of tunnels are able to be created on all Junos devices? (Choose two.)

- A. STP
- B. GRE
- C. IP-IP
- D. IPsec

Correct Answer: BD

Explanation: Junos devices support various types of tunnels for different purposes¹². Option B is correct. Generic Routing Encapsulation (GRE) is a tunneling protocol that can encapsulate a wide variety of network layer protocols inside

virtual point-to-point links over an Internet Protocol network¹. Junos devices support GRE tunnels¹.

Option D is correct. IPsec (Internet Protocol Security) is a protocol suite for securing Internet Protocol (IP) communications by authenticating and encrypting each IP packet of a communication session¹. Junos devices support IPsec tunnels¹.

Option A is incorrect. Spanning Tree Protocol (STP) is not a type of tunnel. It's a network protocol designed to prevent loops in a bridged Ethernet local area network².

Option C is incorrect. While Junos devices do support IP-IP (also known as IP tunneling), it's not supported on all Junos devices¹.

[Latest JN0-351 Dumps](#)

[JN0-351 PDF Dumps](#)

[JN0-351 Exam Questions](#)