



JN0-351^{Q&As}

Enterprise Routing and Switching Specialist (JNCIS-ENT)

Pass Juniper JN0-351 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-351.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What are three requirements to ensure proper GRE or IP-IP tunnel routing? (Choose three.)

- A. Keepalives must be used on stateless tunneling protocols.
- B. Tunnel endpoints must have a route that directs traffic into the tunnel.
- C. BGP must be used on intermediate devices.
- D. Tunnel endpoints must have a valid route to the remote endpoint.
- E. All intermediary devices must have a route to the tunnel endpoints.

Correct Answer: BCD

QUESTION 2

Which two statements about DIS elections in IS-IS are correct? (Choose two.)

- A. If a priority tie occurs, the router with the higher subnetwork point of attachment (SNPA) value becomes the DIS.
- B. The router with the higher priority value becomes the DIS.
- C. The router with the lower priority value becomes the DIS.
- D. If a priority tie occurs, the router with the lower subnetwork point of attachment (SNPA) value becomes the DIS.

Correct Answer: AB

QUESTION 3

Click the Exhibit button.



```
(master:0)[edit]
user@switch-1# show interfaces ge-0/0/5
unit 0 {
  family ethernet-switching {
    vlan {
      members all;
    }
  }
}

(master:0)[edit]
user@switch-1# show vlans
wired {
  vlan-id 10;
}
wireless {
  vlan-id 20;
}

(master:0)[edit]
user@switch-1# commit check
[edit interfaces ge-0/0/5 unit 0 family ethernet-switching vlan]
'members all'
  Access ports cannot specify vlan "all"
error: configuration check-out failed

(master:0)[edit]
user@switch-1#
```

You are building a network and make some configuration changes. While trying to validate these changes, you receive the error shown in the exhibit.

How would you solve this problem?

- A. You must create a new VLAN called all using the VLAN ID of 30.
- B. You must configure the ge-0/0/5.0 interface with family inet instead of family ethernet-switching.
- C. You must configure the port mode as trunk on the ge-0/0/5.0 interface.
- D. You must create two sub-interfaces on ge-0/0/5 with the appropriate VLAN member assigned to each.

Correct Answer: C

QUESTION 4

By default, how long will a learned MAC address be retained in the bridge table on an EX Series switch?

- A. 600 seconds
- B. 3600 seconds
- C. 300 seconds
- D. 1800 seconds

Correct Answer: C

QUESTION 5



Click the Exhibit button.

```
user@router> show ospf neighbor
Address          Interface      State      ID          Pri
  Dead
172.16.248.214   xe-0/0/2.0    2-Way     172.16.248.14 128
  39
```

Referring to the exhibit, which statement is correct?

- A. The router is acting as the DR.
- B. The router is acting as the BDR.
- C. The router is acting as a DROther.
- D. The router is not able to establish an adjacency.

Correct Answer: C

[JN0-351 PDF Dumps](#)

[JN0-351 VCE Dumps](#)

[JN0-351 Exam Questions](#)