



JN0-451^{Q&As}

Mist AI - Specialist (JNCIS-MistAI)

Pass Juniper JN0-451 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-451.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

You are asked to forward event messages from Mist to an external log collector.

In this scenario, which feature would enable this capability?

- A. syslog
- B. webhooks
- C. NETCONF
- D. SNMP traps

Correct Answer: B

QUESTION 2

Click the Exhibit button.

The screenshot shows the 'Security' tab in the Mist interface. It includes filters for 'site: Primary Site', time ranges '1 Hr' and '24 Hrs', and buttons for 'Generate PCI Report' and 'View Client Classification'. Below these are tabs for 'Threats', 'Neighbor APs', 'Approved APs', 'List', and 'Location'. The 'Threats' tab is active, displaying a table of detected threats.

SSID	BSSID	Band	Channel	Avg. RSSI	Seen By	Nearest AP	Location
CS-recnet	[Redacted]		1	-55.9 dBm	1 APs	AP43	Home
Frontier3984	[Redacted]		1	-76.6 dBm	1 APs	AP43	Home
Verizon-5G_Tuna	[Redacted]		1	-79.0 dBm	1 APs	AP43	Home
NETGEAR24	[Redacted]		4	-78.2 dBm	1 APs	AP43	Home
Eero1234	[Redacted]		5	-78.9 dBm	1 APs	AP43	Home
Bob24WiFi	[Redacted]		6	-69.5 dBm	1 APs	AP43	Home

Referring to the exhibit, in the USA, which two statements are correct? (Choose two.)

- A. The WLAN with SSID Eero1234 is not configured to industry best practices.
- B. The WLAN with SSID Eero1234 is configured to industry best practices.
- C. The WLAN with SSID NETGEAR24 is not configured to industry best practices.
- D. The WLAN with SSID NETGEAR24 is configured to industry best practices.

Correct Answer: AC

QUESTION 3



According to the Coverage SLE, which classifier tracks a client that transmits at a lower data rate than the AP to which it is connected?

- A. Asymmetry Downlink
- B. Wi-Fi Interference
- C. Asymmetry Uplink
- D. Slow OKC Roam

Correct Answer: C

QUESTION 4

You are deploying multiple Mist APs across many sites in your network. You must ensure that you apply consistent WxLAN and WLAN policies across all sites within the same organization. Which configuration object should be used to accomplish this behavior?

- A. site labels
- B. an RF template
- C. a device profile
- D. a config template

Correct Answer: B

Reference: https://www.juniper.net/documentation/en_US/junos-space-apps/network-director4.0/topics/concept/wireless-rogue-ap.html

QUESTION 5

What is the AP's role in the IEEE 802.1X authentication process?

- A. It acts as an authenticator.
- B. It acts as a RADIUS proxy server.
- C. It acts as a supplicant.
- D. It acts as an authentication server.

Correct Answer: D

[Latest JN0-451 Dumps](#)

[JN0-451 Practice Test](#)

[JN0-451 Exam Questions](#)