



# JN0-633<sup>Q&As</sup>

Security, Professional (JNCIP-SEC)

## Pass Juniper JN0-633 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-633.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

How does the SRX5800, in transparent mode, signal failover to the connected switches?

- A. It initiates spanning-tree BPDUs.
- B. It sends out gratuitous ARPs.
- C. It flaps the impaired interfaces.
- D. It uses an IP address monitoring configuration.

Correct Answer: B

---

**QUESTION 2**

You want to route traffic between two newly created virtual routers without the use of logical systems using the configuration options on the SRX5800.

Which two methods of forwarding, between virtual routers, would you recommend? (Choose two.)

- A. Use a static route to forward traffic across virtual routers using the next-table option. Enable the return route by using a RIB group. next-table command.
- B. Create static routes in each virtual router using the
- C. Use a RIB group to share the internal routing protocol routes from the master routing instance.
- D. Connect a direct cable between two physical interfaces, one in each virtual router and use next-hop command. static routes with the

Correct Answer: BD

---

**QUESTION 3**

You want to query User Group membership directly using the integrated user firewall services from an Active Directory controller to an SRX Series device.

Which two actions are required? (Choose two.)

- A. Configure the LDAP base distinguished name.
- B. Connect the SRX Series device and the MAG Series device in an enforcer configuration.
- C. Configure a domain name, the username and password of the domain, and the name and IP address of the domain controller in the domain.
- D. Configure the Access Control Service on the MAG Series device for local user authentication and verify that authentication information is transferred between the devices.

Correct Answer: AC

---



#### QUESTION 4

An SRX Series device is configured for inline tap mode.

What will occur if Drop Packet is selected?

- A. The SRX Series device drops a matching packet before it can reach its destination but does not close the connection.
- B. The SRX Series device will ignore the action Drop Packet.
- C. The SRX Series device closes the connection and sends an RST packet to both the client and the server.
- D. The SRX Series device drops a matching packet associated with the connection, preventing traffic for the connection from reaching its destination.

Correct Answer: D

---

#### QUESTION 5

Which statement is true about NAT?

- A. When you implement destination NAT, the router does not apply ALG services.
- B. When you implement destination NAT, the router skips source NAT rules for the initiating traffic flow.
- C. When you implement static NAT, each packet must go through a route lookup.
- D. When you implement static NAT, the router skips destination NAT rules for the initiating traffic flow.

Correct Answer: D

[JN0-633 VCE Dumps](#)

[JN0-633 Practice Test](#)

[JN0-633 Exam Questions](#)