



# JN0-635<sup>Q&As</sup>

Security, Professional

## Pass Juniper JN0-635 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-635.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

A user is unable to reach a necessary resource. You discover the path through the SRX Series device includes several security features. The traffic is not being evaluated by any security policies.

In this scenario, which two components within the flow module would affect the traffic? (Choose two.)

- A. services/ALG
- B. destination NAT
- C. source NAT
- D. route lookup

Correct Answer: BD

---

### QUESTION 2

You are configuring transparent mode on an SRX Series device. You must permit IP-based traffic only, and BPDUs must be restricted to the VLANs from which they originate.

Which configuration accomplishes these objectives?



- A. `bridge {  
block-non-ip-all;  
bypass-non-ip-unicast;  
no-packet-flooding;  
}`
- B. `bridge {  
block-non-ip-all;  
bypass-non-ip-unicast;  
bpdu-vlan-flooding;  
}`
- C. `bridge {  
bypass-non-ip-unicast;  
bpdu-vlan-flooding;  
}`
- D. `bridge {  
block-non-ip-all;  
bpdu-vlan-flooding;  
}`

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: B

Reference: <https://www.oreilly.com/library/view/juniper-srx-series/9781449339029/ch06.html>

---

### QUESTION 3

An administrator wants to implement persistent NAT for an internal resource so that external hosts are able to initiate communications to the resource, with the internal resource having previously sent packets to the external hosts.



Which configuration setting is used to accomplish this goal?

- A. persistent-nat permit any-remote-host
- B. persistent-nat permit target-host-port
- C. address-persistent
- D. persistent-nat permit target-host

Correct Answer: A

---

#### QUESTION 4

You have downloaded and initiated the installation of the application package for the JATP Appliance on an SRX1500. You must confirm that the installation of the application package has completed successfully.

In this scenario, which command would you use to accomplish this task?

- A. show services application-identification version
- B. show services application-identification application detail
- C. show services application-identification application version
- D. show services application-identification status

Correct Answer: D

Reference: [https://www.juniper.net/documentation/en\\_US/junos/topics/topic-map/security-applicationidentification-predefined-signatures.html](https://www.juniper.net/documentation/en_US/junos/topics/topic-map/security-applicationidentification-predefined-signatures.html)

---

#### QUESTION 5

You have configured static NAT for a webserver in your DMZ. Both internal and external users can reach the webserver using the webserver's IP address. However, only internal users can reach the webserver using the webserver's DNS name. When external users attempt to reach the webserver using the webserver's DNS name, an error message is received.

Which action would solve this problem?

- A. Disable Web filtering
- B. Use DNS doctoring
- C. Modify the security policy
- D. Use destination NAT instead of static NAT

Correct Answer: B

Reference: [https://www.juniper.net/documentation/en\\_US/junos/topics/topic-map/security-dns-algs.html](https://www.juniper.net/documentation/en_US/junos/topics/topic-map/security-dns-algs.html)

---



VCE & PDF

Pass4itSure.com

<https://www.pass4itsure.com/jn0-635.html>

2024 Latest pass4itsure JN0-635 PDF and VCE dumps Download

---

[Latest JN0-635 Dumps](#)

[JN0-635 Practice Test](#)

[JN0-635 Exam Questions](#)