



JN0-648^{Q&As}

Enterprise Routing and Switching, Professional (JNCIP-ENT)

Pass Juniper JN0-648 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-648.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Which type of BGP is used to peer with a different autonomous system?

- A. external
- B. classless
- C. dynamic
- D. static

Correct Answer: A

QUESTION 2

You are designing a multicast topology to support IPv4 IPTV broadcasts in your organization. The design should support multiple multicast senders with overlapping group addresses while preventing interference between them. Client devices currently do not support IGMPv3.

Which approach would fulfill these requirements?

- A. Implement MLD.
- B. Assign group addresses in the 224/4 range and implement PIM-DM.
- C. Implement PIM-SM and SSM with SSM maps to support IGMPv2 clients.
- D. Implement bidirectional PIM.

Correct Answer: B

QUESTION 3

Which two statements are true about IS-IS levels? (Choose two.)

- A. Level 1 systems use a default route to reach AS external routes located in other areas.
- B. Level 2 systems must use the loopback address as a part of the ISO network address.
- C. Level 1 systems only form adjacencies with other systems that have different area IDs.
- D. Level 2 systems do not advertise Level 2 routes into a Level 1 area by default.

Correct Answer: AD

**QUESTION 4**

You have multiple BGP routes to the same prefix with equal local-preference values and AS-path lengths. In this scenario, which route will be preferred in the route selection process?

- A. The route with the least preferred origin value.
- B. The route with the lowest MED value.
- C. The route with the most preferred origin value.
- D. The route with the highest MED value.

Correct Answer: C

QUESTION 5

You are currently using VLAN IDs 2 through 300 within your Layer 2 domain and you need to configure VSTP to prevent loops. You must ensure that all VLANs are loop free.

In this scenario, which statement is correct?

- A. You must ensure that the VLANs are balanced between two different root bridges.
- B. You must enable RSTP to account for all VLANs.
- C. You must ensure that the bridge priority is set to the lowest value on all switches in the Layer 2 domain.
- D. You must enable all VLANs, 2 through 300, under the VSTP configuration.

Correct Answer: D

[JN0-648 VCE Dumps](#)

[JN0-648 Practice Test](#)

[JN0-648 Exam Questions](#)