



JN0-662^{Q&As}

Service Provider Routing and Switching - Professional (JNCIP-SP)

Pass Juniper JN0-662 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/jn0-662.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



**QUESTION 1**

Click the Exhibit button.

```
user@host# show protocols ospf
area 0.0.0.6 {
  nssa {
    default-lsa {
      default-metric 10;
      metric-type 1;
      type-7;
    }
  }
  no-summaries;
}
```

Referring to the ABR configuration shown in the exhibit, which two statements are correct? (Choose two.)

- A. The ABR advertises a default route to the NSSA with a metric of 10.
- B. To reach the ABR, routers within the NSSA add 10 to their calculated path cost.
- C. The ABR advertises NSSA routes to the backbone area with a metric of 10.
- D. To reach the ABR, routers within the NSSA use the metric 10 as their path cost.

Correct Answer: A

You must explicitly configure the ABR to generate a default route when attached to a stub or not-stubby-area (NSSA). To inject a default route with a specified metric value into the area, you must configure the default-metric option and specify a metric value.

QUESTION 2

Click the Exhibit button.



```
user@R1> show isis database detail
```

```
IS-IS level 1 Link-state database:
```

```
R1.00-00 Sequence: 0x19, Checksum: 0x3355, Lifetime: 976 secs
```

```
IP prefix: 192.168.16.4/32 Metric: 10 Internal Down
```

```
IP prefix: 192.168.16.5/32 Metric: 10 Internal Down
```

```
IP prefix: 192.168.16.6/32 Metric: 20 Internal Down
```

```
IP prefix: 192.168.16.7/32 Metric: 20 Internal Down
```

```
IS-IS level 2 link-state database:
```

```
R1.00-00 Sequence: 0x1c, Checksum: 0x3355, Lifetime: 976 secs
```

```
IS neighbor: R2.02 Metric: 10
```

```
IS neighbor: R3.02 Metric: 10
```

```
IP prefix: 10.0.0.16/30 Metric: 10 Internal Up
```

```
IP prefix: 10.0.0.20/30 Metric: 10 Internal Up
```

```
IP prefix: 192.168.16.3/32 Metric: 0 Internal Up
```

```
R2.00-00 Sequence: 0x19, Checksum: 0x3355, Lifetime: 973 secs
```

```
IS neighbor: R2.02 Metric: 10
```

```
IS neighbor: R3.03 Metric: 10
```

```
IP prefix: 10.0.0.16/30 Metric: 10 Internal Up
```

```
IP prefix: 10.0.0.24/30 Metric: 10 Internal Up
```

```
IP prefix: 192.168.16.4/32 Metric: 0 Internal Up
```

```
R2.02-00 Sequence: 0x17, Checksum: 0x3355, Lifetime: 973 secs
```

```
IS neighbor: R1.00 Metric: 0
```

```
IS neighbor: R2.00 Metric: 0
```

```
R3.00-00 Sequence: 0x12, Checksum: 0x3355, Lifetime: 973 secs
```

```
IS neighbor: R3.02 Metric: 10
```

```
IS neighbor: R3.03 Metric: 10
```

```
IP prefix: 10.0.0.20/30 Metric: 10 Internal Up
```

```
IP prefix: 10.0.0.24/30 Metric: 10 Internal Up
```

```
IP prefix: 10.0.0.28/30 Metric: 10 Internal Up
```

```
IP prefix: 10.0.0.32/30 Metric: 20 Internal Up
```

```
IP prefix: 10.0.0.36/30 Metric: 10 Internal Up
```

```
IP prefix: 192.168.16.5/32 Metric: 0 Internal Up
```

```
IP prefix: 192.168.16.6/32 Metric: 10 Internal Up
```

```
IP prefix: 192.168.16.7/32 Metric: 10 Internal Up
```

```
R3.02-00 Sequence: 0xb, Checksum: 0x3355, Lifetime: 973 secs
```

```
IS neighbor: R1.00 Metric: 0
```

```
IS neighbor: R3.00 Metric: 0
```

```
R3.03-00 Sequence: 0xb, Checksum: 0x3355, Lifetime: 973 secs
```

```
IS neighbor: R2.00 Metric: 0
```

```
IS neighbor: R3.00 Metric: 0
```

Referring to the exhibit, which statement is correct?



- A. IP address 192.168.16.5 is on a directly connected interface.
- B. Four routes have been leaked from the Level 2 area to the Level 1 area.
- C. The path to IP address 192.168.16.6 is currently unavailable.
- D. R1 has two Level 2 adjacencies and one Level 1 adjacency to other routers.

Correct Answer: A

QUESTION 3

Which two LSA types are permitted in an OSPF stub area? (Choose two.)

- A. Type 1
- B. Type 2
- C. Type 4
- D. Type 5

Correct Answer: AB

Stub areas can contain type 1, 2, and 3 LSAs. A default route is substituted for external routes.

QUESTION 4

You are troubleshooting a Layer 3 VPN issue. The VPN has been passing traffic successfully for some time, but now it is reported that traffic is no longer flowing. You look into the `bgp.l3vpn.0` table and see newly hidden routes.

What would be the cause of this problem?

- A. The LSP used to connect the PE routers is down.
- B. The connection from the PE to the customer is down.
- C. The BGP routes received from the customer are no longer reachable.
- D. The family `inet-vpn` parameter was deleted from the BGP configuration of the PE router.

Correct Answer: D

QUESTION 5

You are asked to configure a new Layer 3 VPN.

In this scenario, which routing-instance type must be used?

- A. vpls



B. evpn

C. vrf

D. 12vpn

Correct Answer: C

[JN0-662 PDF Dumps](#)

[JN0-662 Study Guide](#)

[JN0-662 Braindumps](#)