



# NS0-184<sup>Q&As</sup>

NetApp Certified Storage Installation Engineer, ONTAP

## Pass NetApp NS0-184 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/ns0-184.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

You are installing a new AFF A400 cluster for a customer. The customer indicates that they want to take advantage of AutoSupport On Demand.

In this scenario, which AutoSupport transport protocol must you use?

- A. HTTP
- B. SMTP
- C. FTP
- D. HTTPS

Correct Answer: D

Reference: <https://www.netapp.com/media/10438-tr-4444.pdf> (9)

---

**QUESTION 2**

While installing a new AFF A400 HA pair, you are unable to add an NTP server from another subnet. You are able to ping the NTP server from the new cluster.

In this scenario, what are two causes of this problem? (Choose two.)

- A. The admin SVM has the wrong gateway.
- B. A firewall is blocking port 123.
- C. The time skew is too great.
- D. The cluster management LIF needs to be in a different IPspace.

Correct Answer: AD

---

**QUESTION 3**

You installed a new pair of Cisco 92300YC cluster switches at a customer's site. Before you install any files on the switch, you want to view the current configuration.

In this scenario, which command would you use to accomplish this task?

- A. switchcfgshow
- B. fabricshow
- C. config show
- D. show running-config



Correct Answer: A

---

#### QUESTION 4

You are adding new controllers to an existing cluster. As part of the upgrade process, you have updated the BES-53248 cluster switches.

In this scenario. Which two commands would you use to verify a healthy cluster after the upgrade? (Choose two.)

- A. network port show -ipspace Cluster
- B. network interface show -vserver Cluster
- C. network device-discovery show -protocol cdp
- D. network interface show -vserver Cluster -fields auto-revert

Correct Answer: AB

Reference: <https://docs.netapp.com/platstor/index.jsp?topic=%2Fcom.netapp.doc.hw-sw-ix8-setup%2FGUID-340F5F50-FFDA-4B5C-A151-007CF9D6063B.html>

---

#### QUESTION 5

You use the system health subsystem show command to troubleshoot your newly installed ONTAP cluster.

In this scenario, which two health outputs would this command show you? (Choose two.)

- A. data switch cabling
- B. cluster switch cabling
- C. shelf connectivity
- D. node CPU utilization

Correct Answer: CD

Reference: <https://www.doc-developpement-durable.org/file/Projets-informatiques/cours-and-manuelsinformatiques/Netapp/Data%20ONTAP%208.0%207-Mode%20System%20Administration%20Guide.pdf>

[NS0-184 VCE Dumps](#)

[NS0-184 Study Guide](#)

[NS0-184 Braindumps](#)