



NS0-506^{Q&As}

NetApp Certified Implementation Engineer - SAN, Clustered Data
ONTAP

Pass NetApp NS0-506 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/ns0-506.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

What is a NetApp-recommended zoning best practice?

- A. Switch port zoning should always be employed.
- B. WWNN zoning is required.
- C. Single-initiator zoning is recommended.
- D. Zones can overlap.

Correct Answer: C

QUESTION 2

Exhibit

```
cl01::> net int show -vserver svm1 (network interface show) Logical Status Network Current Current Is Vserver Interface
Admin/Oper Address/Mask Node Port Home
```

```
svm1 fc_lif1 up/up 20:0b:00:a0:98:4e:ba:14 cl01-01 3a true fc_lif2 up/up 20:0c:00:a0:98:4e:ba:14 cl01-02 3a true lif1
up/up 172.16.21.31/24 cl01-01 a0a true
```

```
lif2 up/up 172.16.21.32/24 cl01-02 a0a true 4 entries were displayed. cl01::>
```

Referring to the exhibit, a customer needs to move LIF "fc_lif1" to a new port.

Which three actions must be performed to accomplish this task? (Choose three.)

- A. Remove LIF from the existing portset.
- B. Quiesce all hosts accessing LUNs over the LIF.
- C. Take the LIF offline.
- D. Update the switch zone to include the new WWPN.
- E. Move the LIF to a new home port using the network interfacemodify command.

Correct Answer: CDE

QUESTION 3

After mapping the LUN on the cluster, you are not able to see in on the Windows 2012 host.

```
cl01::>igroup show -instance Vserver Name: svm1 Igroup Name: ig1-win Protocol: iscsi OS Type: Windows Portset
Binding Igroup: Igroup UUID: 358338ba-cfd611df-a9ab-123478563412 Initiators: iqn.199105.com.microsoft: host1 (not
logged in)
```

Referring to the exhibit, what is the problem?



- A. An administrator is not logged into the host.
- B. The iSCSI target has not been added to the host.
- C. The OS type should be windows_2008.
- D. The OS type should be windows_gpt.

Correct Answer: B

QUESTION 4

Exhibit

You have a 2-node data ONTAP 8.3 cluster.

Based on the exhibit, which change must be made to make svm1 conform to iSCSI best practices?

```
cl01::> net int show -vserver svm1 -data -protocol iscsi Logical Status Network Current Current Is Vserver Interface
Admin/Oper Address/Mask Node Port Home
```

```
svm1 up/up 10.204.34.25/24 cl01-01 a0a 434 true cl01::>iscsi show -vserver svm1 Vserver: svm1 Target Name:
iqn.1992 08.com.netapp: sn.ca5eaa069c211 Target Alias: svm1 Administrative Status: up
```

- A. The iSCSI LIFs must be moved to a VLAN higher than 1024.
- B. An iSCSI LIF must be added to node cl01-02.
- C. The Target Alias must be modified to match the Target Name.
- D. The iSCSI LIFs must be moved to a physical interface; iSCSI LIFs are not supported on top of an ifgrp.

Correct Answer: C

QUESTION 5

Which information-gathering command should you use to gather logs for troubleshooting switch information for your Brocade switches?

- A. cfgshow
- B. fabricshow
- C. configshow
- D. supportsave

Correct Answer: B