



# NS0-515<sup>Q&As</sup>

NetApp Certified Implementation Engineer - SAN, E-Series

## Pass NetApp NS0-515 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/ns0-515.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

A company is using the Federal Information Processing Standard (FIPS) on all volume groups. However, one volume group failed a security audit.

In this scenario what would cause a volume group to fail the security audit?

- A. An FDE drive was added as a spare in the volume group
- B. Data Assurance was changed to "disabled" for the volume group
- C. The Secure Erase operation was applied to the volume group disks
- D. Connectivity to the key server was interrupted

Correct Answer: A

Reference: [https://mysupport.netapp.com/NOW/public/eseries/sam\\_archive1150/index.html#page/GUID8538272A-B802-49D9-9EA2-96C82DAD26A2/GUID-8C172D9A-53B5-4CCD-A327-08E4F538E783.html](https://mysupport.netapp.com/NOW/public/eseries/sam_archive1150/index.html#page/GUID8538272A-B802-49D9-9EA2-96C82DAD26A2/GUID-8C172D9A-53B5-4CCD-A327-08E4F538E783.html)

---

**QUESTION 2**

What are two methods for setting the host protocol configuration on the E2800 controller with a 4-port 16Gbps FC or 10Gbps iSCSI SFP+ host interface card (HIC)? (Choose two.)

- A. Set at the factory, based on the order
- B. Change the QSFP type in the HIC
- C. Change the Feature Pack in the SANtricity System Manager
- D. Set in the Hardware tab using SANtricity System Manager

Correct Answer: CD

Reference: <https://docs.netapp.com/ess-11/index.jsp?topic=%2Fcom.netapp.doc.e-2800-sysmaint%2FGUID-C2A2AAC4-A1B9-468F-8CE8-862D32917840.html>

---

**QUESTION 3**

Which alerting method would be configured using the SANtricity System Manager setup wizard?

- A. Syslog
- B. SNMP
- C. Web Services Proxy
- D. Email

Correct Answer: B



Reference: <https://docs.oracle.com/cd/E19298-01/CRCM1573/CRCM1573.pdf>

---

#### QUESTION 4

What is represented by the Headroom graph on the SANtricity System Manager performance tab?

- A. the percentage of I/O associated with the backend disk drives
- B. the remaining performance capability of the physical objects in the storage system
- C. the percentage of CPU processing capacity that is being used by the operations on the system
- D. the resources that are being consumed by a defined workload

Correct Answer: B

Reference: [https://mysupport.netapp.com/NOW/public/eseries/sam\\_archive1130/GUID-8538272A-B80249D9-9EA2-96C82DAD26A2/GUID-8538272A-B802-49D9-9EA2-96C82DAD26A2\\_2.pdf](https://mysupport.netapp.com/NOW/public/eseries/sam_archive1130/GUID-8538272A-B80249D9-9EA2-96C82DAD26A2/GUID-8538272A-B802-49D9-9EA2-96C82DAD26A2_2.pdf) (379)

---

#### QUESTION 5

Your company has deployed an E2824 and has decided to change the host protocol from iSCSI to FC. You use the storage array profile to review the installed SFPs.

In this scenario, which set of supported data rates indicates that you are using dual-purpose SFPs?

- A. 25 Gbps, 10 Gbps
- B. 32 Gbps, 16 Gbps, 8 Gbps, 4 Gbps
- C. 16 Gbps, 10 Gbps, 8 Gbps, 4 Gbps
- D. 16 Gbps, 8 Gbps, 4 Gbps

Correct Answer: C

Reference: [https://library.netapp.com/ecm/ecm\\_download\\_file/ECMLP2773527](https://library.netapp.com/ecm/ecm_download_file/ECMLP2773527) (2)

[Latest NS0-515 Dumps](#)

[NS0-515 Exam Questions](#)

[NS0-515 Braindumps](#)